

**NORTH 1/16<sup>TH</sup> CORNER NORTHWEST QUARTER SECTION 17, TOWNSHIP 19 SOUTH, RANGE 12 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 1 OF THE 7<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 148 DATED JANUARY 8, 1872 TO FIND THE CORNERS TO THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 8-19-12 AND 20 ACRES OFF THE SOUTH LINE OF THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 8, SAID THAT **HE FOUND THE STONE** AT THE 1/2/4 CORNER ON THE SOUTH LINE OF THE SOUTHWEST 1/4 OF SECTION 8 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 440' NORTH TO THE SET PERMANENT SOUTHEAST CORNER OF A 10 ACRE LOT – HE DID NOT INDICATE WHAT HE SET FOR THIS CORNER
- 2) 1,658' NORTH TO A 4" DIAMETER MULBERRY POST SET FOR THE PERMANENT CORNER TO THE 20 ACRE LOT
- 3) 2,656' NORTH TO THE STONE HE FOUND AT THE 1/2/4 CORNER ON THE NORTH SIDE OF THE SW1/4 OF SECTION 8

- 2) AI CHAMNESS, SURVEYOR DEPUTIZED BY O. D. HENRY, COUNTY ENGINEER OF LYON COUNTY, KANSAS, FOR AN OFFICIAL SURVEY OF FOUR TRACTS IN THE SOUTHWEST 1/4 OF SECTION 8-19-12 RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 105 WITH THE SURVEY COMPLETED AND FILED ON APRIL 13, 1935, SAID THAT **HE** LOCATED THE 1/4/4 CORNER ON THE SOUTH SIDE OF THE SOUTHWEST 1/4 OF SECTION 8 ON LINE AND HALFWAY BETWEEN THE 1" IRON PIN HE FOUND AT THE SOUTHWEST CORNER AND THE TEMPORARY MARK HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 8 ON THIS **PERMANENT SURVEY**. A NOTE IN THE UPPER LEFT CORNER STATES: PLAINTIFFS EXHIBIT NUMBER 1, CASE NUMBER 19824, 5-13-38.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,316.5' WEST TO THE SOUTHWEST CORNER OF SECTION 8 HE IDENTIFIED ON HIS SURVEY DRAWING AS A 1" IRON PIN IN THE CONCRETE SLAB
- 2) 1,316.5' EAST TO A TEMPORARY MARK HE MADE ON THE PAVEMENT OF U.S. 50 SOUTH FOR THE SOUTH 1/4 CORNER OF SECTION 8 AS PER NOTES BY YINGLING, OF OFFICIAL SURVEY OF RECORD IN THE COUNTY ENGINEERS OFFICE
- 3) 434.94' (±) TO A 3" X 8' X 47" LIMESTONE HE SET
- 4) 660.00' NORTH TO A 5-1/2" X 3-1/2" 31" LIMESTONE HE SET
- 5) 943.09' NORTH TO A 4" X 6" X 32" LIMESTONE HE SET
- 6) 990.00' NORTH TO A 4" X 6" X 32" LIMESTONE HE SET
- 7) 1,014.74' NORTH TO A 4" X 6" X 27" LIMESTONE HE SET

- 3) FRANCIS PERRIER, ASSISTANT COUNTY ENGINEER, IN A SURVEY MADE NOVEMBER 14, 1935, TO ESTABLISH A TOWNSHIP ROAD IN SECTION 8-19-12, THE "TIMMONS-KORTE" ROAD, RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 107, APPARENTLY FOUND THE STONE AT THE 1/4/4 CORNER ON THE SOUTH SIDE OF THE SOUTHWEST CORNER OF SECTION 8 ON THIS ROAD SURVEY. HE NOTED THAT THE SURVEY PARTY CONSISTED OF O. D. HENRY, COUNTY ENGINEER, F. J. PERRIER, ASSISTANT COUNTY ENGINEER, AND ED O'CONNELL, COUNTY COMMISSIONER.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 990' NORTH TO A LIMESTONE SET BY A PREVIOUS SURVEY ON PAGE 105 IN PERMANENT SURVEY BOOK 1 TO BEGIN THIS ROAD SURVEY TO THE NORTH

NORTH SIXTEENTH CORNER NORTHWEST QUARTER 17-19-12