

**WEST 1/4 CORNER SECTION 17, TOWNSHIP 19 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 538 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 14" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 17 & 18-19-12.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 21 RECORDED IN SURVEY BOOK "A" ON PAGE 117 DATED FEBRUARY 28 & 29, 1868 FOR A SURVEY OF A. HENSHAW'S AND M. WEAVER'S LAND, BEING A DIVISION FO THE WEST 1/2 OF THE NORTHEAST 1/4 AND 20 ACRES ON THE SOUTH END OF THE EAST 1/2 OF THE EAST 1/2 OF THE NORTHEAST 1/4 OF SECTION 17-19-12, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 17-19-12 ON THIS SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 320 RODS EAST TO THE STONE HE SET FOR THE EAST 1/4 CORNER OF SECTION 17-19-12
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 67 RECORDED IN SURVEY BOOK "A" ON PAGE 167 DATED AUGUST 24, 1868 FOR A SURVEY OF LAND OWNED BY J. W. LANCE AND OTHER LYING IN SECTION 18-19-12, TO SURVEY THE WEST 1/2 OF THE NORTHEAST 1/4 OF SAID SECTION 18, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 18-19-12 ON THIS SURVEY.
- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "C" ON PAGES 66 & 67 FOR ROAD NUMBER 279 ON A PETITION BY ANDREW HENSHAW [PACKET 555 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] DATED OCTOBER 1884, SAID THAT THIS ROAD CROSSES THE K. C. & E. RAILROAD AT A POINT 215 FEET SOUTH OF THE WEST 1/4 CORNER OF SECTION 17-19-12.
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 24, 2004, FOR PROJECT NUMBER 04408-02, SURVEY F18003 IN THE SURVEY FILE FOR TOWNSHIP 19-12 TO MARK THE NORTH AND WEST LINES OF THE EAST HALF OF THE SOUTHEAST QUARTER OF SECTION 18-19-12 LYING NORTH OF THE RAILROAD, SAID THAT HE DETERMINED THAT THE EAST 1/4 CORNER OF SECTION 18-19-12 WAS **LOST**. **HE SET A 1" X 6" CARRIAGE BOLT** FOR THE EAST 1/4 CORNER OF SECTION 18-19-12 ON TRUE LINE AND HALF WAY BETWEEN THE NORTHEAST CORNER OF SECTION 18-19-12 AND THE SOUTHEAST CORNER OF SECTION 18-19-112.
  - 1) **30.0' WEST TO A 1/2" REBAR WITH HIS CAP SET**
  - 2) 11.6' ENE TO THE TOP CENTER OF THE EAST END OF A METAL PIPE
  - 3) 11.35' WNW TO THE CENTER OF A CHANNEL POST FOR AN OBJECT MARKER SIGN
  - 4) 12.0' ESE TO THE CENTER OF A CHANNEL POST FOR AN OBJECT MARKER SIGN
  - 5) 1.5' NORTH TO THE CENTERLINE OF A METAL PIPE RUNNING EAST-WEST
  - 6) 1.5' EAST TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD "P" NORTH-SOUTHHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,653.91' NORTH TO THE 1" PIN HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 18-19-12
  - 2) 2,653.92' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 18-19-12
  - 3) 1,321.76' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 18-19-12

HIS INFORMATION IS CONTINUED ON PAGE 2

- 4) 2,643.52' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 18-19-12
- 5) 5,151.05' WEST TO THE STONE AND REBAR HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 18-19-12

WEST QUARTER CORNER 17-19-12