

**WEST 1/16<sup>TH</sup> CORNER SOUTHWEST QUARTER SECTION 19, TOWNSHIP 19 SOUTH,  
RANGE 12 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 21, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 21 DATED MARCH 23, 1870 TO DIVIDE THE SOUTHEAST 1/4 OF SECTION 24-19-11 EQUALLY BY A LINE RUNNING NORTH & SOUTH AND PART OFF 20 ACRES FORM THE EAST OF THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 24, SAID THAT **HE SET A STONE** FOR THE PERMANENT EAST 1/2/4 OF THE SOUTHEAST 1/4 OF SECTION 24-19-11 ON THE RANGE LINE AND HALFWAY BETWEEN THE STONES THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 24-19-11 AND THE SOUTHEAST CORNER OF SECTION 24-19-11 ON THIS **PERMANENT SURVEY**.

**HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:**

- 1) 1,319' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 24-19-11
  - 2) 1,319' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-19-11
  - 3) 660' WEST TO THE SOUTHWEST CORNER OF THE 20 ACRE LOT – HE DID NOT INDICATE WHAT HE SET TO MARK THE CORNER
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 22, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 22 DATED MARCH 23, 1870 TO FIND THE CENTER OF THE SOUTHWEST FRACTIONAL 1/4 CORNER OF SECTION 19-19-12 AND ESTABLISH THE 1/2/4 CORNER ON THE NORTH SIDE OF THE SOUTHWEST 1/4 OF SECTION 19, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/2/4 CORNER OF THE SOUTHWEST 1/4 OF SECTIONS 19-19-12 ON THE RANGE LINE BETWEEN RANGES 11 & 12 ON THIS **PERMANENT SURVEY**.

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F24009 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR THE SURVEY OF TWO TRACTS IN SECTION 24-19-11, FOR PROJECT NUMBER 98021-02 DATED FEBRUARY 2, 1998, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A COTTON GIN SPIKE** FOR THE NORTHEAST CORNER OF THE SOUTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 24-19-11 ON THE RANGE LINE AND HALFWAY BETWEEN THE EAST 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 24-19-11.

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,320.64' NORTH ON THE RANGE LINE TO THE LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 24-19-11
- 2) 165.00' SOUTH ON THE RANGE LINE TO THE COTTON GIN SPIKE HE SET FOR THE SOUTHEAST CORNER OF THE "EAST TRACT" AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 25.00' WEST ON THE WEST RIGHT-OF-WAY LINE OF COUNTY ROAD "N"
- 3) 1,320.63' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR OVER THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 24-19-11
- 4) 25.00' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET ON THE WEST RIGHT-OF-WAY LINE OF COUNTY ROAD "N"
- 5) 165.00' WEST TO THE NORTHWEST CORNER OF THE "EAST TRACT"
- 6) 265.00' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE "WEST TRACT"
- 7) 2,666.58' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE S1/2 OF THE SE1/4 OF SECTION 24-19-11

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 19-19-12