

NORTH 1/4 CORNER SECTION 21, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ON PAGE 531 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 16 & 21-19-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.72 CHAINS WEST TO THE 21" X 15" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-19-12
 - 2) 39.72 CHAINS EAST TO THE 19" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-19-12

- 2) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F16004 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR A SURVEY TO LOCATE THE NORTH AND WEST LINES OF THE SOUTHEAST 1/4 OF SECTION 16-19-12 DATED MARCH 31, 1977 SHOWS ON HIS SURVEY DRAWING ON AN AERIAL PHOTOGRAPH THAT **HE SET A PIN** FOR THE SOUTH 1/4 CORNER OF SECTION 16-19-12 HALFWAY BETWEEN THE "MONUMENT" AT THE SOUTHEAST CORNER OF SECTION 16-19-12 AND THE CORNER STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 16-19-12. THERE ARE NO TIES ON THE SURVEY. **VERIFY BEFORE USING AND CHECK FOR THE STONE OF RECORD = WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
HIS DRAWING SHOWS THE FOLLOWING DISTANCES:
 - 1) 2,628' WEST TO A MONUMENT AT THE SOUTHWEST CORNER OF SECTION 16, BEING 100 FEET NORTH OF THE NORTH TRACT
 - 2) 2,628' EAST TO THE CORNER STONE FOUND AT THE SOUTHEAST CORNER OF SECTION 16
 - 3) 2,636' NORTH TO THE CORNER SET FOR THE CENTER OF SECTION 16

- 3) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-12 SHOWS AN **IRON PIN** AT THE "S 1/4 CORNER SECTION 16-19-12". **VERIFY BEFORE USING AND CHECK FOR THE STONE OF RECORD - WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 41' SW TO A SPIKE IN A TELEPHONE POLE
 - 2) 23.35' NW TO A SPIKE IN THE TOP OF A POST

NORTH QUARTER CORNER 21-19-12