

NORTH 1/4 CORNER SECTION 24, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ON PAGE 512 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 11" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 13 & 24-19-12, FROM WHICH:
 - 1) AN ELM TREE 12" IN DIAMETER BEARS N. 50° W. AT 12 LINKS DISTANCE
 - 2) AN ELM TREE 24" IN DIAMETER BEARS S. 85° E. AT 15 LINKS DISTANCE

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

 - 1) 39.75 CHAINS WEST TO THE 24" X 10" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13, 14, 23 & 24-19-12
 - 2) 39.75 CHAINS EAST TO A 20" X 10" X 3-1/2" LIMESTONE SET FOR THE CORNER TO SECTIONS 13 & 24-19-12 ON THE EAST TOWNSHIP LINE

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 27 RECORDED IN SURVEY BOOK "A" ON PAGE 122 DATED MARCH 18, 1868 AT THE REQUEST OF JAMES OGDEN TO RUN THE TRUE LINE OF THE NORTH BOUNDARY OF SECTION 24-19-12 FROM THE NORTHWEST CORNER TO THE NORTH 1/4 CORNER, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 24-19-12 ON THIS SURVEY.

- 3) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 47, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 46 DATED MAY 14 & 25, 1870 TO ESTABLISH THE CENTER OF SECTION 24-19-12 AND ALSO TO DIVIDE THE SOUTHWEST 1/4 INTO EQUAL HALVES BY A LINE RUNNING NORTH & SOUTH, SAID THAT **HE FOUND THE 1/4 SECTION CORNER** ON THE NORTH LINE OF SECTION 24-19-12 ON THIS **PERMANENT SURVEY**.

HIS NOTES SHOWS THE FOLLOWING INFORMATION:

 - 1) 5,325' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 24-19-12

NORTH QUARTER CORNER 24-19-12