

**NORTH 1/16<sup>TH</sup> CORNER SOUTHWEST QUARTER SECTION 24, TOWNSHIP 19 SOUTH,  
RANGE 12 EAST**

- 1) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 47, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 46 DATED MAY 14 & 25, 1870 TO ESTABLISH THE CENTER CORNER OF SECTION 24-19-12 AND ALSO TO DIVIDE THE SOUTHWEST 1/4 INTO EQUAL HALVES BY A LINE RUNNING NORTH & SOUTH, SAID THAT **HE SET A LIMESTONE** FOR THE PERMANENT 1/2/4 CORNER ON THE NORTH SIDE OF THE SOUTHWEST 1/4 OF SECTION 24-19-12 ON THIS **PERMANENT SURVEY**.
- 2) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A ROAD SURVEY FOR ROAD NUMBER 719 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 76 PETITIONED BY JOHN C. VANGUNDY AND OTHERS FOR A ROAD IN SECTION 24-19-12 THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND COUNTY SURVEYOR ON APRIL 26, 1923, AND WAS ORDERED ALLOWED ON JANUARY 28, 1924, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 24 TO BEGIN THIS ROAD SURVEY.

**HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:**

- 1) BEGINNING AT THE STONE AT THE SOUTHWEST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 24-19-12, HE USED AS A FORESIGHT THE 1/2 SECTION STONE ON THE WEST LINE OF SECTION 24-19-12; THENCE PROCEEDED IN RUNNING THE CENTER LINE OF THE ROAD PETITIONED FOR AS FOLLOWS: S. 80°00' W. FOR 658 FEET TO A STONE; THENCE N. 33°00' W. FOR 143 FEET TO A STONE HE SET; THENCE N. 48°46' W. FOR 129.7 FEET TO A STONE HE SET; THENCE N. 40°22' W. FOR 358.3 FEET TO A STONE HE SET; THENCE 67°33' W. FOR 650 FEET TO A STONE HE SET; THENCE N. 55°03' W. FOR 386.7' TO A STONE HE SET, THIS POINT AT THE INTERSECTION OF THIS SURVEY WITH THE EAST RIGHT-OF-WY LINE OF THE PRESENT LAID OUT ROAD AND THE TERMINUS OF THIS ROAD SURVEY
- 2) ROAD TO BE 40 FEET WIDE, 20 FEET EACH SIDE OF THE CENTER LINE AS SURVEYED

NORTH SIXTEENTH CORNER SOUTHWEST QUARTER 24-19-12