

**CENTER CORNER OF NORTHWEST QUARTER OF SECTION 27, TOWNSHIP 19 SOUTH,
RANGE 12 EAST**

- 1) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 92, AN **AGREEMENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 92 DATED MARCH 27 & 28, 1885 BY THE ORDER OF OSCAR SHAFER TO LOCATE THE CORNERS OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 27-19-12, SAID THAT **HE SET A 4" X 4" X 12" STONE** FOR THE CENTER OF THE NORTHWEST CORNER OF SECTION 27 ON THIS **AGREEMENT SURVEY**. HE SAID THAT THE AGREEMENT TO ABIDE BY THIS SURVEY WAS FILED IN THE OFFICE OF THE REGISTER OF DEEDS ON APRIL 6, 1885.
 - 1) A 3" DIAMETER HICKORY TREE IS SOUTH 70° WEST AT 3 FEET DISTANCE
 - 2) A 2.5" DIAMETER HICKORY TREE IS NORTH 13° EAST AT 5.6 FEET DISTANCE
 - 3) A 3" RED BUD TREE IS NORTH 90° EAST AT 7 FEET DISTANCE

HIS SURVEY NOTES SHOWS THE FOLLOWING DISTANCES:

 - 1) 658' WEST TO A LIMESTONE 6" IN THE CENTER, RUNNING TO A POINT ON BOTH ENDS, 18" LONG AND TRIANGULAR IN SHAPE HE SET FOR THE SOUTHEAST CORNER OF THE E1/2 OF THE NW1/4 OF THE NW1/4 OF SECTION 27
 - 2) 1,316' WEST TO A TEMPORARY STAKE HE SET FOR THE 1/8TH CORNER ON THE WEST SIDE OF THE NW1/4 OF SECTION 27
 - 3) 1,316' EAST TO A TEMPORARY STAKE HE SET FOR THE 1/8TH CORNER ON THE EAST SIDE OF THE NW1/4 OF SECTION 27

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F27001 IN THE SURVEY FILE FOR TOWNSHIP 19-12 TO MONUMENT THE WEST HALF OF THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 27-19-12 LYING SOUTH TO THE OLD M. K. & T. RAILWAY NOW ABANDONED FOR PROJECT NUMBER 99012-02 DATED JUNE 22, 1999 SAID IN HIS *REPORT OF SURVEY* SAID THAT HE EXCAVATED THE STONE AT THE SOUTHEAST CORNER OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 27 THAT WAS SET BY EDMISTON IN 1885 IN SURVEY BOOK "E" ON PAGE 92, BUT HE DID **NOT** FIND IT. HE DETERMINED A **THEORETICAL POSITION** FOR THE CENTER OF THE NORTHWEST 1/4 OF SECTION 27 TO BE AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/16TH CORNERS, BUT HE DID **NOT** MONUMENT THIS POSITION. HE NOTED IN HIS *SURVEY NOTES*: "THIS AREA AND THIS SECTION IN PARTICULAR [SECTION 27] HAS KNOWN GLO FRAUD AS EVIDENCED BY PREVIOUS SURVEYS."

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:

 - 1) 660.95' WEST TO A 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF THE NW1/4 OF SECTION 27
 - 2) 1,321.90' WEST TO A 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/4 CORNER OF SECTION 27
 - 3) 1,327.88' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE E1/2 OF THE NW1/4 OF THE NW1/4 OF SECTION 27 THAT WAS SET BY EDMISTON IN 1885
 - 4) 1,321.90' EAST TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 27
 - 5) 1,327.88' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 27

CENTER OF NORTHWEST QUARTER OF SECTION 27-19-12