

**WEST 1/16TH CORNER NORTHEAST QUARTER SECTION 27, TOWNSHIP 19 SOUTH,
RANGE 12 EAST**

- 1) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 92, AN **AGREEMENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 92 DATED MARCH 27 & 28, 1885 BY THE ORDER OF OSCAR SHAFER TO LOCATE THE CORNERS OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 27-19-12, SAID THAT HE SET A **TEMPORARY STAKE** FOR THE EAST 1/8TH CORNER THE NORTHWEST 1/4 OF SECTION 27-19-12 ON LINE AND HALFWAY BETWEEN THE STONES THAT HE FOUND AT THE NORTH 1/4 CORNER AND THE CENTER CORNER OF SECTION 27-19-12 ON THIS **AGREEMENT SURVEY**. HE SAID THAT THE AGREEMENT TO ABIDE BY THIS SURVEY WAS FILED IN THE OFFICE OF THE REGISTER OF DEEDS ON APRIL 6, 1885.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,330.8' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 27-19-12
 - 2) 1,330.8' SOUTH TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 27-19-12
 - 3) 1,316' WEST TO THE 4" X 4" X 12" LIMESTONE MARKED "1/8" HE SET FOR THE CENTER CORNER OF THE NW1/4 OF SECTION 27-19-12
 - 4) 1,874' WEST TO THE LIMESTONE 6" IN THE CENTER, RUNNING TO A POINT ON BOTH ENDS, 18" LONG AND TRIANGULAR IN SHAPE MARKED "1/16" HE SET FOR THE SOUTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF THE NW1/4 OF SECTION 27-19-12
 - 5) 2,632' WEST TO THE TEMPORARY STAKE HE SET FOR THE WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 27-19-12
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F27001 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR PROJECT NUMBER 99012-02 DATED JUNE 22, 1999 SHOWS ON HIS SURVEY DRAWING THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE NORTHWEST 1/4 OF SECTION 27-19-12 TO BE ON LINE AND HALFWAY BETWEEN THE NORTH 1/4 CORNER AND THE CENTER CORNER OF SECTION 27-19-12, BUT THE POSITION WAS **NOT** MONUMENTED ON THIS SURVEY. HE NOTED IN HIS *SURVEY NOTES*: "THIS AREA AND THIS SECTION IN PARTICULAR [SECTION 27] HAS KNOWN GLO FRAUD AS EVIDENCED BY PREVIOUS SURVEYS."
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 1,321.90' WEST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 27-19-12
 - 2) 1,982.85' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF THE NW1/4 OF SECTION 27-19-12
 - 3) 2,643.80' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/4 CORNER OF SECTION 27-19-12
 - 4) 1,328.79' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 27-19-12
 - 5) 1,328.79' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE CENTER CORNER OF SECTION 27-19-12
 - 6) 3,984.30' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTH 1/4 CORNER OF SECTION 27-19-12

WEST SIXTEENTH CORNER NORTHEAST QUARTER 27-19-12