

WEST 1/16TH CORNER NORTHWEST QUARTER SECTION 27, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 89, A PERMANENT SURVEY RECORDED IN SURVEY BOOK "C" ON PAGE 11 TO FIND THAT PART OF THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 27-19-12 LYING EAST OF THE CHANNEL OF COAL CREEK DATED MARCH 1873, SAID THAT HE SET A TEMPORARY POINT FOR THE EAST 1/2/4 CORNER OF THE NORTHEAST 1/4 OF SECTION 27-19-12 ON THIS **PERMANENT SURVEY**. **[NOTE: HE NOTED AN ERROR IN THE DESCRIPTION THAT THIS SURVEY WAS IN THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 28-19-12, MAKING THIS CORNER THE EAST 1/2/4 CORNER OF THE NORTHEAST 1/4 OF SECTION 28-19-12 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, BY MATTHEW BROWN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 92, AN **AGREEMENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 92 DATED MARCH 27 & 28, 1885 BY THE ORDER OF OSCAR SHAFER TO LOCATE THE CORNERS OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 27-19-12, SAID THAT HE SET A TEMPORARY STAKE FOR THE WEST 1/8TH CORNER OF THE NORTHWEST 1/4 OF SECTION 27-18-12 ON THIS **AGREEMENT SURVEY**. HE SAID THAT THE AGREEMENT TO ABIDE BY THIS SURVEY WAS FILED IN THE OFFICE OF THE REGISTER OF DEEDS ON APRIL 6, 1885. **HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:**
 - 1) 658' EAST TO THE LIMESTONE 6" IN THE CENTER RUNNING TO A POINT ON EACH END, 18" LONG, AND TRIANGULAR IN SHAPE HE SET FOR THE SOUTHEAST CORNER OF THE E1/2 OF THE NW1/4 OF THE NW1/4 OF SEC. 27-19-12
 - 2) 1,316' EAST TO THE 4" X 4" X 12" LIMESTONE HE SET FOR THE CENTER CORNER OF THE NW1/4 OF SECTION 27-19-12
 - 3) 2,632' EAST TO THE TEMPORARY STAKE HE SET FOR THE EAST 1/8TH CORNER OF THE NE1/4 OF SECTION 27-19-12

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F27001 IN THE SURVEY FILE FOR TOWNSHIP 19-12 DATED JUNE 22, 2009 FOR PROJECT NUMBER 99012-02, TO MONUMENT THE WEST HALF OF THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 27-19-12 LYING SOUTH OF THE OLD M. K. & T. RAILWAY NOW ABANDONED, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 27-19-12 ON LINE AND HALFWAY BETWEEN THE NORTHWEST CORNER AND THE WEST 1/4 CORNER OF SECTION 27-19-12. HE NOTED IN HIS *SURVEY NOTES*: "THIS AREA AND THIS SECTION IN PARTICULAR [SECTION 27] HAS KNOWN GLO FRAUD AS EVIDENCED BY PREVIOUS SURVEYS."
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,275.37' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET IN THE CENTERLINE OF THE ABANDONED MK&T RAILROAD
 - 2) 1,326.97' NORTH TO THE 1/2" REBAR HE FOUND OVER THE GLO STONE AT THE NORTHWEST CORNER OF SECTION 27-19-12
 - 3) 1,326.97' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/4 CORNER OF SECTION 27-19-12
 - 4) 3,980.90' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-19-12
 - 5) 660.95' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF THE NW1/4 OF SECTION 27-19-12

HIS INFORMATION IS CONTINUED ON PAGE 2

- 6) 1,321.90' EAST TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF THE E1/2 OF THE NW1/4 OF THE NW1/4 OF SECTION 27-19-12
- 7) 2,643.80' EAST TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 27-19-12

WEST SIXTEENTH CORNER NORTHWEST QUARTER 27-19-12