

NORTH 1/4 CORNER SECTION 28, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ON PAGE 530 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 21 & 28-19-12 ON FEBRUARY 28, 1857.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.72-1/2 CHAINS WEST TO THE 28" X 13" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-19-12
 - 2) 39.72-1/2 CHAINS EAST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 21, 22, 27 & 28-19-12
- 2) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 4, 1999, FOR JOB NUMBER 99498-02, SURVEY F28002 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR THE SURVEY OF TWO TRACTS LYING SOUTH OF THE COTTONWOOD RIVER IN THE SOUTHWEST QUARTER OF THE SOUTHEAST QUARTER OF SECTION 28-19-12, SAID THAT SHE EXCAVATED WITH A COUNTY MAINTAINER AT THE POSITION FOR THE NORTH 1/4 CORNER OF SECTION 28-19-12 BASED ON THE POSITION EXPECTED ACCORDING TO HER RESEARCH DATA AND FIELD TRAVERSE, BUT SHE DID **NOT** FIND THE STONE. SHE CONSIDERED THAT THIS CORNER WAS **LOST**. **SHE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTH 1/4 CORNER OF SECTION 28-19-12 ON LINE AND AT 1/2 THE DISTANCE BETWEEN THE NORTHWEST & NORTHEAST CORNERS OF SECTION 28-19-12.
- 1) 1.0' NORTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST
 - 2) 20.85' SE TO A 1/2" X 24" REBAR WITH A "GEOTECH, INC." CAP REFERENCE BAR
 - 3) 16.0' SW TO A 1/2" X 24" REBAR WITH A "GEOTECH, INC." CAP REFERENCE BAR
 - 4) 15.8' NW TO A 1/2" X 24" REBAR WITH A "GEOTECH, INC." CAP REFERENCE BAR
- HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 2,636.48' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP PLACED OVER THE GLO STONE SHE FOUND AT THE NORTHWEST CORNER OF SEC. 28-19-12
 - 2) 2,636.48' EAST TO THE 1/2" REBAR THROUGH TO THE STONE SHE FOUND AT THE NORTHEAST CORNER OF SECTION 28-19-12
 - 3) 2,653.27' SOUTH TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 28-19-12
 - 4) 3,979.67' SOUTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 28-19-12
 - 5) 5,306.08' SOUTH TO THE 1/2" REBAR SHE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 28-19-12

NORTH QUARTER CORNER 28-19-12