

**WEST 1/16<sup>TH</sup> CORNER SOUTHEAST QUARTER SECTION 28, TOWNSHIP 19 SOUTH, RANGE 12 EAST**

1) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED NOVEMBER 4, 1999, FOR JOB NUMBER 99498-02, SURVEY F28002 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR THE SURVEY OF TWO TRACTS LYING SOUTH OF THE COTTONWOOD RIVER IN THE SOUTHWEST QUARTER OF THE SOUTHEAST QUARTER OF SECTION 28-19-12, SAID THAT **SHE SET A 1/2" X 24" REBAR WITH HER "LS 1130" CAP** FOR THE NORTHWEST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 28-19-12 AT ONE-HALF THE DISTANCE AND ON LINE BETWEEN THE CENTER CORNER AND THE SOUTH QUARTER CORNER OF SECTION 28-19-12.

- 1) 80.5' WSW TO A 40 D NAIL IN A 2.5' DIAMETER ELM TREE AT THE CROP LINE
- 2) 24.45' SOUTH TO A 40 D NAIL IN A 1.0' DIAMETER ELM TREE
- 3) 8.0' SOUTH TO A LINE OF CULTIVATION RUNNING EAST & WEST

**HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,326.41' SOUTH TO THE 1/2" REBAR SHE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 28-19-12
- 2) 1,326.40' NORTH TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 28-19-12
- 3) 3,979.67' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTH 1/4 CORNER OF SECTION 28-19-12
- 4) 1,317.46' EAST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE CENTER CORNER OF THE SE1/4 OF SECTION 28-19-12
- 5) 2,634.92' EAST TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 28-19-12

WEST SIXTEENTH CORNER SOUTHEAST QUARTER 28-19-12