

NORTH 1/4 CORNER SECTION 29, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ON PAGE 536 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 29-19-12 ON MARCH 10, 1857. THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.67-1/2 CHAINS WEST TO THE 24" X 13" X 2-1/2 LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-19-12
 - 2) 39.67-1/2 CHAINS EAST TO THE 28" X 13" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-19-12

- 2) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-12 STATES THAT THEY DUG A 3 FOOT DEEP AREA FOR THE STONE AT THIS CORNER ON APRIL 12, 1972, AND THAT **NO EVIDENCE OF A STONE WAS FOUND**, AT THE "N1/4 CORNER SECTION 29-19-12".

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 6, 2001, FOR PROJECT NUMBER 01349-02, SURVEY F29006 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR THE SURVEY OF A 32 ACRE TRACT IN THE SOUTHEAST QUARTER OF SECTION 32-19-12, SAID THAT HE EXCAVATED WITH A COUNTY BACKHOE AND A COUNTY MAINTAINER OVER A WIDE AREA FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 29-19-12, BUT HE DID **NOT** FIND THE STONE. HE DEEMED THIS CORNER WAS **LOST** IN BOTH POSITIONS. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTH 1/4 CORNER OF SECTION 29-19-12 ON LINE AND HALFWAY BETWEEN THE NORTHWEST AND NORTHEAST CORNERS OF SECTION 29-19-12.
 - 1) 29.3' NNW TO THE TOP CENTER OF THE WEST END OF A CASING
 - 2) 32.4' NNE TO THE TOP CENTER OF THE EAST END OF A CASING
 - 3) 48.2' ESE TO THE NORTH END OF A OM-2 CHANNEL POST AT THE GROUND
 - 4) 4.0' EAST TO THE CENTERLINE TRAVELED WAY OF AN ENTRANCE TO THE NORTH
 - 5) 4.5' NORTH TO THE CENTERLINE TRAVELED WAY OF EAST-WEST GRAVEL ROAD 150HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,625.08' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-19-12
 - 2) 2,625.07' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 29-19-12
 - 3) 5,315.21' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 29-19-12

- 4) JAMES A. BRULL, P.S. 1475, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 21, 2015 FOR COUNTY PROJECT NUMBER 15-46, SAID THAT **HE FOUND THE EXISTING RECORD 5/8" REBAR WITH A LYON COUNTY CAP AT 0.45 FEET DEEP** AT THE NORTH 1/4 CORNER OF SECTION 29-19-12 FROM THE EXISTING REFERENCES ON FILE AT THE LYON COUNTY SURVEYORS OFFICE BY STEVEN S. BROSEMER, P.S. 752, DATED NOVEMBER 6, 2001. THIS SECTION CORNER IS AT PROJECT STATION 0+00.00.
 - 1) 29.6' NNW TO THE TOP CENTER OF THE WEST END OF A STEEL CASING ENTRANCE CULVERT
 - 2) 32.6' NNE TO THE TOP CENTER OF THE EAST END OF A STEEL CASING ENTRANCE CULVERT
 - 3) 45.0' ESE TO THE NORTH END OF AN OM-2 CHANNEL POST AT THE GROUND
 - 4) 158.45' ENE TO A MAG NAIL & WASHER SET IN THE SOUTH FACE OF A POWER POLE

HIS TIES ARE CONTINUED ON PAGE 2

- 5) 4.5' EAST TO THE CENTERLINE OF THE TRAVELED WAY OF A STEEL CASING ENTRANCE CULVERT TO THE NORTH
- 6) 7.0' NORTH TO THE CENTERLINE OF THE TRAVELED WAY OF GRAVEL ROAD 150 EAST-WEST

COUNTY PROJECT 15-46 PLANS SHOW THE FOLLOWING INFORMATION:

- 1) 1,599.90' EAST TO THE 5/8" X 1' REBAR WITH A LYON COUNTY CAP AT 0.4' DEEP AT CENTERLINE STATION 15+99.90
- 2) 2,000.23' EAST TO THE 5/8" X 1' REBAR WITH A LYON COUNTY CAP AT 0.37' DEEP AT CENTERLINE STATION 20+00.23
- 3) 2,625.02' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP AT 0.65' DEEP OVER THE GLO STONE AT THE NORTHEAST CORNER OF SECTION 29-19-12 AT CENTERLINE STATION 26+25.02

NORTH QUARTER CORNER 29-19-12