

**CENTER CORNER OF SECTION 30, TOWNSHIP 19 SOUTH, RANGE 12 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 39, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 39 DATED JUNE 4-6, 1870 TO ESTABLISH THE 1/4 CORNER BETWEEN SECTIONS 29 & 30, THE 1/4 CORNER BETWEEN SECTION 19 & 30, AND TO SET TEMPORARY 1/2-1/4 CORNERS AND THE CENTER CORNER ON THE NORTH & SOUTH CENTER LINE OF SECTION 30-19-12, SAID THAT **HE SET A STONE** FOR THE PERMANENT CENTER CORNER OF SECTION 30-19-12 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 30 AND THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 30 ON THIS **PERMANENT SURVEY**.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,327' NORTH TO THE STONE HE SET FOR THE PERMANENT 1/2-1/4 CORNER ON THE WEST SIDE OF THE NE1/4 OF SECTION 30-19-12
  - 2) 2,654' NORTH TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 30-19-12
  - 3) 1,327' SOUTH TO THE STONE HE SET FOR THE PERMANENT 1/2-1/4 CORNER ON THE WEST SIDE OF THE SE1/4 OF SECTION 30-19-12
  - 4) 2,654' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 30-19-12
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 65 TO LOCATE AND PERMANENTLY ESTABLISH THE WEST LINE OF THE SOUTHEAST 1/4 OF SECTION 30-19-12 ORDERED BY THE LYON COUNTY BOARD OF COUNTY COMMISSIONERS, JOB NUMBER 94178-02, SAID THAT HE DETERMINED THE **THEORETICAL POSITION** FOR THE CENTER CORNER OF SECTION 30 TO BE AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS ON THIS **PERMANENT SURVEY**. THE FIELD WORK WAS CONDUCTED FROM JUNE 20 TO JULY 15; HE SIGNED IT ON OCTOBER 11; AND IT WAS FILED ON NOVEMBER 14, 1994.

HIS DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,649.24' NORTH TO THE 1/2" REBAR HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 30-19-12 THAT HE SET ON A PREVIOUS SURVEY
- 2) 2,6538.06' EAST TO THE GLO STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 30-19-12
- 3) 1,325.93' SOUTH TO THE TRUE POSITION FOR THE 1/16<sup>TH</sup> CORNER AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 25,93 FEET SOUTH OF THE TRUE POSITION
- 4) 2,650.77' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 30-19-12
- 5) 2,560.09' WEST TO THE THEORETICAL POSITION FOR THE WEST 1/4 CORNER OF SECTION 30-19-12 ON THE RANGE LINE

CENTER OF SECTION 30-19-12