

NORTH 1/4 CORNER SECTION 30, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ON PAGE 537 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 30-19-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 38.60 CHAINS WEST TO THE 22" X 12" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-19-12 ON THE WEST TOWNSHIP BOUNDARY
 - 2) 40.00 CHAINS EAST TO THE 24" X 13" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-19-12

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 22, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 22 DATED MARCH 23, 1870 TO FIND THE CENTER OF THE SOUTHWEST FRACTIONAL 1/4 CORNER OF SECTION 19-19-12 AND ESTABLISH THE 1/2/4 CORNER ON THE NORTH SIDE OF THE SOUTHWEST 1/4 OF SAID SECTION 19, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF FRACTIONAL SECTION 19-19-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,318.75' NORTH TO THE TEMPORARY STAKE HE SET FOR THE EAST 1/2/4 CORNER OF THE SW1/4 OF SECTION 19-19-12
 - 2) 2,637.5' NORTH TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 19-19-12

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 39, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 39 DATED JUNE 4-6, 1870 TO ESTABLISH THE 1/4 CORNER BETWEEN SECTIONS 29 & 30, THE 1/4 CORNER BETWEEN SECTION 19 & 30, AND TO SET TEMPORARY 1/2/4 CORNERS AND THE CENTER CORNER ON THE NORTH & SOUTH CENTER LINE OF SECTION 30-19-12, SAID THAT **HE FOUND A STONE** AT THE NORTH 1/4 CORNER OF SECTION 30-19-12 "**ALREADY SET**" AT 2,641' WEST OF THE NORTHEAST CORNER OF SECTION 30-19-12. HE RAN THE SECTION LINE FROM THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 30-19-12 WEST TO THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-19-12 ON THE RANGE LINE, AND SAID THAT HE 'MADE THE PROPER CORRECTIONS AND ESTABLISHED THE 1/4 CORNER AND SET A STONE' FOR THE NORTH 1/4 CORNER OF SECTION 30-19-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,640' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 30-19-12
 - 2) 2,196' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-19-12 ON THE RANGE LINE
 - 3) 1,327' SOUTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE NE1/4 OF SECTION 30-19-12
 - 4) 2,654' SOUTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 30-19-12
 - 5) 3,981' SOUTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE SE1/4 OF SECTION 30-19-12
 - 6) 5,308' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 30-19-12

- 4) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 3, 1989, SAID THAT HE CONSIDERED THAT THE SOUTH 1/4 CORNER OF SECTION 19-19-12 WAS **LOST**. **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 19-19-12.

HIS TIES ARE ON PAGE 2

- 1) 31.25' NW TO A PK NAIL & WASHER IN A POWER POLE
 - 2) 57.7' NE TO A PK NAIL & WASHER IN A CEDAR TREE
 - 3) 81.4' WSW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
 - 4) 3.2' NORTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 65 TO LOCATE AND PERMANENTLY ESTABLISH THE WEST LINE OF THE SOUTHEAST 1/4 OF SECTION 30-19-12 ORDERED BY THE LYON COUNTY BOARD OF COUNTY COMMISSIONERS, JOB NUMBER 94178-02, SAID THAT **HE FOUND THE 1/2" REBAR WITH HIS RED "LS 752" CAP** AT THE NORTH 1/4 CORNER OF SECTION 30-19-12 THAT HE SET IN 1998 ON A PREVIOUS SURVEY ON THIS **PERMANENT SURVEY**. HE FOUND THIS CAPPED REBAR FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE. THE FIELD WORK WAS CONDUCTED FROM JUNE 20 TO JULY 15; HE SIGNED IT ON OCTOBER 11; AND IT WAS FILED ON NOVEMBER 14, 1994.
- 1) 31.2' NW TO A 40 D SPIKE & WASHER IN A POWER POLE
 - 2) 57.9' SSE TO A 40 D SPIKE & WASHER IN AN 8" ELM TREE [THE START OF A TREE LINE TO THE SOUTH]
 - 3) 3.5' NORTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST-WEST
 - 4) 30.0' NE TO THE EAST END OF A 24" STEEL DRAINAGE PIPE
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,549.73' WEST TO THE 5/8" REBAR OVER THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 30-19-12 ON THE RANGE LINE
 - 2) 2,641.77' EAST TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 30-19-12, THAT HE SET IN 1988 TO REPLACE A CHARRED STAKE THAT HE FOUND
 - 3) 2,649.24' SOUTH TO THE THEORETICAL LOCATION FOR THE CENTER CORNER OF SECTION 30-19-12
 - 4) 3,974.63' SOUTH TO THE TRUE POSITION FOR THE 1/16TH CORNER, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 23.59' SOUTH OF THE **TRUE POSITION**
 - 5) 5,300.01' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 30-19-12

NORTH QUARTER CORNER 30-19-12