

**WEST 1/16TH CORNER NORTHEAST QUARTER SECTION 30, TOWNSHIP 19 SOUTH,
RANGE 12 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 39, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 39 DATED JUNE 4-6, 1870 TO ESTABLISH THE 1/4 CORNER BETWEEN SECTIONS 29 & 30, THE 1/4 CORNER BETWEEN SECTION 19 & 30, AND TO SET TEMPORARY 1/2/4 CORNERS AND THE CENTER CORNER ON THE NORTH & SOUTH CENTER LINE OF SECTION 30-19-12, SAID THAT **HE SET A STONE** FOR THE WEST 1/2/4 CORNER ON THE WEST SIDE OF THE NORTHEAST 1/4 OF SECTION 30 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 30-19-12 AND THE STONE THAT HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 30-19-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,327' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 30-19-12
 - 2) 1,327' SOUTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 30-19-12
 - 3) 2,654' SOUTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE SE1/4 OF SECTION 30-19-12
 - 4) 3,981' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 30-19-12

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 114 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 36 DATED JULY 17 & 18, 1873 TO DIVIDE THE SOUTH 1/2 OF THE NORTHEAST 1/4 AND THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 30-19-12 INTO CERTAIN PARTS BY RUNNING LINES NORTH AND SOUTH, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/2/4 CORNER OF THE NORTHEAST 1/4 OF SECTION 30-19-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 2,632.0' EAST TO THE STONE HE FOUND AT THE EAST 1/2/4 CORNER OF THE NE1/4 OF SECTION 30-19-12

WEST SIXTEENTH CORNER NORTHEAST QUARTER 30-19-12