

WEST 1/16TH CORNER SOUTHEAST QUARTER SECTION 30, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 39, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 39 DATED JUNE 4-6, 1870 TO ESTABLISH THE 1/4 CORNER BETWEEN SECTIONS 29 & 30, THE 1/4 CORNER BETWEEN SECTION 19 & 30, AND TO SET TEMPORARY 1/2/4 CORNERS AND THE CENTER CORNER ON THE NORTH & SOUTH CENTER LINE OF SECTION 30, ALL IN TOWNSHIP 19-12, SAID THAT **HE SET A STONE** FOR THE WEST 1/2/4 CORNER OF THE SOUTHEAST 1/4 OF SECTION 30-19-12 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER AND THE STONE THAT HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 30-19-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,327' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 30-19-12
- 2) 1,327' NORTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 30-19-12
- 3) 2,654' NORTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE NE1/4 OF SECTION 30-19-12
- 4) 3,981' NORTH TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 30-19-12

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 114 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 36 DATED JULY 17 & 18, 1873 TO DIVIDE THE SOUTH 1/2 OF THE NORTHEAST 1/4 AND THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 30-19-12 INTO CERTAIN PARTS BY RUNNING LINES NORTH AND SOUTH, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/2/4 OF THE SOUTHEAST 1/4 OF SECTION 30-19-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 2,644.0' EAST TO THE STONE HE FOUND AT THE EAST 1/2/4 CORNER OF THE SE1/4 OF SECTION 30-19-12

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 65 TO LOCATE AND PERMANENTLY ESTABLISH THE WEST LINE OF THE SOUTHEAST 1/4 OF SECTION 30-19-12 ORDERED BY THE LYON COUNTY BOARD OF COUNTY COMMISSIONERS, JOB NUMBER 94178-02, SAID THAT HE DETERMINED THE LOCATION FOR THE WEST 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 30-19-12 TO BE AT THE POINT HALFWAY BETWEEN THE THEORETICAL LOCATION FOR THE CENTER CORNER OF SECTION 30-19-12 AND THE 1/2" REBAR WITH HIS "LS 752" CAP THAT HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 30-9-12 ON THIS **PERMANENT SURVEY**. **HE SET A 1/2" REBAR WITH HIS "LS 752" CAP AS A WITNESS CORNER AT 25.39 FEET SOUTH OF THE TRUE POSITION ON THE SOUTH BANK OF THE COTTONWOOD RIVER**, OR 1,300.00 FEET NORTH OF THE SOUTH 1/4 CORNER OF SECTION 30-19-12. THE FIELD WORK WAS CONDUCTED FROM JUNE 20 TO JULY 15; HE SIGNED IT ON OCTOBER 11, AND IT WAS FILED ON NOVEMBER 14, 1994.

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES TO THE TRUE CORNER:

- 1) 25.39' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE **WITNESS CORNER**
- 2) 1,325.39' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE PERMANENT SOUTH 1/4 CORNER OF SECTION 30-19-12

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 1,325.39' NORTH TO THE THEORETICAL LOCATION FOR THE CENTER CORNER OF SECTION 30-19-12
- 4) 3,974.63' NORTH TO THE 1/2" REBAR HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 30-19-12 FROM HIS PREVIOUS SURVEY

WEST SIXTEENTH CORNER SOUTHEAST QUARTER 30-19-12