

**WEST 1/16<sup>TH</sup> CORNER NORTHWEST QUARTER OF SECTION 31, TOWNSHIP 19 SOUTH,  
RANGE 12 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGE 204 [PACKET 39 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY B. F. PARKER AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 19-11 & 19-12 THAT HE SURVEYED ON JULY 15, 1872, AND WAS ORDERED ESTABLISHED AS A 40 FOOT WIDE ROAD AT A MEETING HELD BY THE COUNTY BOARD ON OCTOBER 7, 1872 AS ATTESTED BY DAVID S. GILMORE, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE WEST 1/16<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 31-19-12 ON THE RANGE LINE ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE 1/2/4 LINE TO A TURN TO THE SOUTH-WESTERLY IN THE NE1/4 OF SECTION 36-19-11
  - 2) THIS ROAD EXTENDS EAST ON THE 1/2/4 LINE TO THE CENTER CORNER OF THE NW1/4 OF SECTION 31-19-12 AT A TURN TO THE NORTH
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED SEPTEMBER 30, 2005, FOR PROJECT NUMBER 05313-02, SURVEY F36009 IN THE SURVEY FILE FOR SECTIONS 17-36 IN TOWNSHIP 19-11 FOR A SURVEY OF THE NORTH HALF OF THE NORTHEAST QUARTER OF SECTION 36-19-11 FOR JAYLENE ARNETT, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 36-19-11 ON THE RANGE LINE AND HALFWAY BETWEEN THE NORTHEAST CORNER AND THE EAST QUARTER CORNER OF SECTION 36-19-11.
- 1) 22.40' NNW TO A CONCRETE NAIL & WASHER IN THE EAST GATE POST
  - 2) 31.85' NW TO A CONCRETE NAIL & WASHER IN THE WEST GATE POST
  - 3) 47.0' SW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
  - 4) 17.5' WEST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "N" TO THE NORTH
  - 5) 2.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 137 EAST-WEST
  - 6) 5.5' WEST TO A LINE OF FENCE TO THE NORTH EXTENDED
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,319.03' NORTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SEC. 36-19-11
  - 2) 659.51' SOUTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE S1/2 OF THE SE1/4 OF THE NE1/4 OF SECTION 36-19-11 AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 40' WEST
  - 3) 1,319.03' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 36-19-11
  - 4) 3,957.09' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP IN A MONUMENT WELL HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 36-19-11

WEST SIXTEENTH CORNER NORTHWEST QUARTER SECTION 31-19-12