

NORTH 1/4 CORNER SECTION 33, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ON PAGE 529 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 18" X 2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 28 & 33-19-12.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 39.82-1/2 CHAINS WEST TO THE 29" X 14" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-19-12
 - 2) 39.82-1/2 CHAINS EAST TO THE 22" X 9" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-19-12
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 19 RECORDED IN SURVEY BOOK "A" ON PAGE 116 DATED FEBRUARY 25, 1868 FOR A SURVEY FOR T. MARTIN & J. ROBINSON TO ESTABLISH THE CENTER OF SECTION 33-19-12, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 33-19-12 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 320 RODS, 10 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 33-19-12 ON THE TOWNSHIP LINE
- 3) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F28001 IN THE SURVEY FILE FOR TOWNSHIP 19-12 TO LOCATE AND ESTABLISH THE CORNERS TO A TRACT OF LAND LOCATED IN THE SOUTHWEST QUARTER OF SECTION 28-19-12 LYING SOUTH OF THE COTTONWOOD RIVER FOR BRIDGES DATED MAY 11, 1973, HE SHOWS ON HIS SURVEY DRAWING A "**MONUMENT**" AT THE SOUTHEAST CORNER OF THE SOUTHWEST 1/4 OF SECTION 28-19-12 AT HALFWAY BETWEEN THE "MONUMENTS" AT THE SOUTHWEST AND SOUTHEAST CORNERS OF SECTION 28. THIS SECTION CORNER IS ALSO THE SOUTHEAST CORNER OF THE BRIDGES TRACT. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,071.35' WEST TO THE "MONUMENT" HE SET AT THE SOUTHWEST CORNER OF BRIDGES TRACT – NOT DESCRIBED
 - 2) 2,634' WEST TO THE "MONUMENT" AT THE SOUTHWEST CORNER OF SECTION 28-19-12 – NOT DESCRIBED
 - 3) 2,634' EAST TO THE "MONUMENT" AT THE SOUTHEAST CORNER OF SECTION 28-19-12 – NOT DESCRIBED
- 4) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 4, 1999, FOR JOB NUMBER 99498-02, SURVEY F28002 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR THE SURVEY OF TWO TRACTS LYING SOUTH OF THE COTTONWOOD RIVER IN THE SOUTHWEST QUARTER OF THE SOUTHEAST QUARTER OF SECTION 28-19-12, SAID THAT **SHE FOUND A 1/2" REBAR ATTRIBUTABLE TO LESLIE M. GOULD** AT THE SOUTH 1/4 CORNER OF SECTION 28-19-12 PER RESEARCH AT THE COUNTY ENGINEER'S OFFICE.
- 1) 2.25' WEST TO A LINE OF FENCE TO THE SOUTH [EXTENDED TO THE NORTH]
 - 2) 21.6' NORTH TO A LINE OF FENCE RUNNING EAST & WEST ON THE NORTH SIDE OF COUNTY ROAD 140
 - 3) 21.95' NORTH TO A 40 D NAIL & WASHER IN AN OLD CORNER FENCE POST
 - 4) 27.75' NE TO THE TOP CENTER OF THE NORTH END OF A CORRUGATED METAL PIPE CULVERT
 - 5) 39.45' SOUTH TO A 40 D NAIL & WASHER IN THE WEST FACE OF A 1.5' DIAMETER ELM TREE

HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

HER INFORMATION IS CONTINUED ON PAGE 2

- 1) 2,634.25' WEST TO THE 1/2" REBAR SHE FOUND ON THIS SURVEY AT THE SOUTHWEST CORNER OF SECTION 28-19-12
 - 2) 1,317.20' EAST TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 28-19-12
 - 3) 2,634.40' EAST TO THE 1/2" REBAR SHE FOUND AT THE SOUTHEAST CORNER OF SECTION 28-19-12
 - 4) 1,326.41' NORTH TO THE 1/2" REBAR WITH HER "LS 1130" CAP SHE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 28-19-12
 - 5) 2,652.81' NORTH TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF SECTION 28-19-12
 - 6) 5,306.08' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP SHE SET FOR THE NORTH 1/4 CORNER OF SECTION 28-19-12
- 5) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN SURVEY F28003 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR THE RE-SURVEY OF A TRACT OF LAND LYING IN THE SOUTHEAST QUARTER OF SECTION 29 AND A TRACT LYING IN THE SOUTHWEST QUARTER OF SECTION 28, ALL IN TOWNSHIP 19-12 FOR PROJECT NUMBER 99513-02 DATED APRIL 26, 2000 SHOWS THAT **SHE FOUND THE 1/2" REBAR ATTRIBUTABLE TO L. M. GOULD, L.S. 142** AT THE SOUTH 1/4 CORNER OF SECTION 28-19-12 FROM HER EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEERS OFFICE DATE NOVEMBER 1999. HER SECTION CORNER REPORT FOR PROJECT 99498-02 REFERENCED THIS PROJECT NUMBER ALSO.
- 1) 2.25' WEST TO A LINE OF FENCE TO THE SOUTH [EXTENDED TO THE NORTH]
 - 2) 21.6' NORTH TO A LINE OF FENCE RUNNING EAST & WEST ON THE NORTH SIDE OF COUNTY ROAD 140
 - 3) 21.95' NORTH TO A 40 D NAIL & WASHER IN AN OLD CORNER FENCE POST
 - 4) 27.75' NE TO THE TOP CENTER OF THE NORTH END OF A CORRUGATED METAL PIPE CULVERT
 - 5) 39.45' SOUTH TO A 40 D NAIL & WASHER IN THE WEST FACE OF A 1.5' DIAMETER ELM TREE
- HER SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,071.68' WEST TO THE 1/2" REBAR SHE FOUND AT THE SOUTHEAST CORNER OF TRACT 2, ATTRIBUTABLE TO L. M. GOULD
 - 2) 2,634.26' WEST TO THE SQUARE 1/2" REBAR SHE FOUND AT THE SOUTHEAST CORNER OF SECTION 29-19-12
 - 3) 2,902.15' WEST TO THE 1/2" REBAR SHE FOUND AT THE SOUTHWEST CORNER OF TRACT 1, ATTRIBUTABLE TO L. M. GOULD
 - 4) 3,950.12' WEST TO THE 1/2" REBAR SHE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 [OF THE SE1/4] OF SECTION 29-19-12, ATTRIBUTABLE TO L. M. GOULD

NORTH QUARTER CORNER 33-19-12