

**NORTH 1/16TH CORNER NORTHEAST QUARTER SECTION 33, TOWNSHIP 19 SOUTH,
RANGE 12 EAST**

- 1) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED NOVEMBER 4, 1999, FOR PROJECT NUMBER 99513-02, SAID THAT **SHE SET A 1/2" X 24" REBAR WITH HER "LS 1130" CAP** FOR THE SOUTH 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 28 AT ONE-HALF THE DISTANCE AND ON LINE BETWEEN THE SOUTH QUARTER CORNER AND THE SOUTHEAST CORNER OF SECTION 28.
 - 1) 18.8' ENE TO A 40 D NAIL IN A 0.8' DIAMETER WALNUT TREE
 - 2) 45.0' WEST TO A 40 D NAIL IN A 1.0' DIAMETER WALNUT TREE
 - 3) 10.05' SOUTH TO THE CENTERLINE TRAVELED WAY OF ROAD 140 RUNNING EAST & WEST

- 2) POLLY A. JONES, L.S. 1130, DEPUTY COUNTY SURVEYOR, IN SURVEY F28002 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR THE SURVEY OF TWO TRACTS IN THE SOUTHWEST QUARTER OF THE SOUTHEAST QUARTER OF SECTION 28-19-12 FOR PROJECT NUMBER 99498-02 DATED MARCH 21, 2000 SHOWS ON HER SURVEY DRAWING THAT **SHE SET A 1/2" REBAR WITH HER "LS 1130" CAP** FOR THE SOUTH 1/16TH CORNER OF THE SOUTHEAST 1/4 OF SECTION 28 ON LINE AND HALFWAY BETWEEN THE SOUTH 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 28.
HER SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:
 - 1) 1,317.30' EAST TO A 1/2" REBAR FOUND AT THE SOUTHEAST CORNER OF SEC. 28
 - 2) 1,317.20' WEST TO A 1/2" REBAR FOUND AT THE SOUTH 1/4 CORNER OF SEC. 28
 - 3) 3,951.45' WEST TO A 1/2" REBAR FOUND AT THE SOUTHWEST CORNER OF SECTION 28
 - 4) 1,326.67' NORTH TO A 1/2" REBAR WITH HER "LS 1130" CAP SET FOR THE CENTER OF THE SE1/4 OF SECTION 28
 - 5) 2,653.34' NORTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE NE1/4 OF THE SE1/4 OF SECTION 28

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 33-19-12