

WEST 1/4 CORNER SECTION 33, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ON PAGE 528 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 32 & 33-19-12.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 19 RECORDED IN SURVEY BOOK "A" ON PAGE 116 DATED FEBRUARY 25, 1868 FOR A SURVEY FOR T. MARTIN & J. ROBINSON TO ESTABLISH THE CENTER OF SECTION 33-19-12, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 33-19-12 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 319 RODS, 4 LINKS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 33-19-12
- 3) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 40
ON NOVEMBER 2, 1914 A PETITION SIGNED BY E. E. LEWIS AND OTHERS FOR THE LOCATION OF A ROAD IN TOWNSHIP 19-11 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON DECEMBER 14, 1914, AND THE FINAL ORDER WAS ISSUED ON JANUARY 8, 1915.
 - 1) BEGINNING AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 33-19-12; FROM THENCE EAST ON THE NORTH LINE OF THE SAID QUARTER SECTION 80 RODS MORE OR LESS AND TERMINATING ON THE WEST LINE OF THE NORTHEAST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 33-19-12
 - 2) ROAD TO BE GRANTED AS A **PRIVATE ROAD 25 FEET WIDE** OFF OF THE NORTH END OF THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 33-19-12
- 4) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 691 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 48 PETITIONED BY E. E. LEWIS AND OTHERS FOR A ROAD IN SECTION 33-19-12 [PACKET 847 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND COUNTY SURVEYOR ON DECEMBER 14, 1914 AND WAS GRANTED AS A **PRIVATE ROAD 25 FEET WIDE** OFF OF THE NORTH END OF THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 33-19-12, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF THE NORTHWEST 1/4 OF THE SOUTHWEST 1/4 OF SECTION 33-19-12 ON THIS ROAD SURVEY.
HIS NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) BEGINNING AT A STONE SET IN THE GROUND AT **25 FEET SOUTH** OF THE NORTHWEST CORNER OF THE NW1/4 OF THE SW1/4 OF SECTION 33-19-12, FROM THENCE EASTERLY 25 FEET SOUTH OF THE NORTH LINE OF THE NW1/4 OF THE SW1/4 OF SAID SECTION 33 TO A **STONE SET IN A HEDGE FENCE 25 FEET SOUTH** OF THE NORTHEAST CORNER OF SAID NW1/4 OF THE SW1/4 OF SECTION 33-19-12, A DISTANCE OF 1,329.24 FEET
- 5) MARION WAYNE BLACKBOURN, L.S. 1127, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 29, 1994, FOR JOB NUMBER 93-12-054, LARGE SURVEY SR#32001 IN THE SURVEY DRAWER FOR TOWNSHIP 19-12, SAID THAT **HE FOUND A 5/8" REBAR AT 1" BELOW THE GRAVEL SURFACE** AT THE EAST 1/4 CORNER OF SECTION 32-19-13. HE SAID THAT THE REBAR POSITION CHECKS WITHIN A REASONABLE TOLERANCE FOR DISTANCE AND THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER, AND THAT PERMANENT SURVEY NOTES AT THE LYON COUNTY ENGINEER'S OFFICE FOR SECTION 33-19-12 WOULD INDICATE THIS CORNER HAD BEEN OF LONG STANDING WITH PERPETUATING

EVIDENCE OF SURVEYS CONDUCTED FROM THIS POINT. **HE ACCEPTED THE 5/8" REBAR AS THE LOCATION** FOR THE EAST 1/4 CORNER OF SECTION 32-19-12.

- 1) 33.0' NW TO THE SOUTH END OF A 24" DIAMETER CULVERT PIPE
- 2) 118.3' NNE TO A MASONRY NAIL SET IN A POWER POLE
- 3) 135.5' SSE TO A MASONRY NAIL SET IN A POWER POLE
- 4) 3.2' EAST TO THE CENTERLINE TRAVELED WAY OF THE NORTH-SOUTH GRAVEL ROAD

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,653.29' NORTH TO THE NORTHEAST CORNER OF SECTION 32-19-12
- 2) 2,650.71' SOUTH TO THE SOUTHEAST CORNER OF SECTION 32-19-12 ON THE TOWNSHIP LINE
- 3) 2,628.69' WEST TO THE CENTER CORNER OF SECTION 32-19-12
- 4) 3,945.67' WEST TO THE NORTH 1/16TH CORNER OF THE SW1/4 OF SEC. 32-19-12
- 5) 5,262.64' WEST TO THE WEST 1/4 CORNER OF SECTION 32-19-12

WEST QUARTER CORNER 33-19-12