

**NORTH 1/4 CORNER SECTION 34, TOWNSHIP 19 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 523 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 9" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 34-19-12.  
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THERE APPEARS TO BE AN ERROR IN THE DISTANCES IN THE ORIGINAL GLO NOTES. THE DISTANCE TO THE NORTHEAST CORNER OF SECTION 34-19-12 IS 79.87 CHAINS. THE NOTES SAID THAT THEY SET A 24" X 9" X 5" LIMESTONE FOR THE 1/4 SECTION CORNER AT **39.73-1/2 CHAINS** WEST OF THE NORTHEAST CORNER, WHILE HALF WAY WOULD BE **39.93-1/2 CHAINS**.
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 128 OF THE 7<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 50 TO ESTABLISH THE CENTER CORNER AND FIND THE AREA OF THAT PART OF THE SOUTHWEST 1/4 OF SECTION 27-19-12 SOUTH OF THE COTTONWOOD RIVER DATED DECEMBER 29, 1873, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 27-19-12 ON THIS **PERMANENT SURVEY**.
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 25 OF THE 8<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 80 DATED MAY 20, 1874 TO SUBDIVIDE THE SOUTHWEST 1/4 OF SECTION 34-19-12 INTO EAST AND WEST HALVES, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 34-19-12 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 5,284' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 34-19-12 ON THE TOWNSHIP LINE
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F34002 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR A 57.3 ACRE TRACT IN THE NORTH HALF OF THE SOUTHWEST QUARTER OF SECTION 34-19-12 DATED OCTOBER 31, 1988 FOR PROJECT NUMBER 88219, SAID IN HIS *REPORT OF SURVEY* THAT THE NORTH 1/4 CORNER OF SECTION 34-19-12 WAS DEEMED **LOST** AS IT FALLS IN CULTIVATION. HE DETERMINED A **THEORETICAL POSITION** FOR THE NORTH 1/4 CORNER OF SECTION 34-19-12 TO BE ON LINE AND HALFWAY BETWEEN THE NORTHWEST AND NORTHEAST CORNERS OF SECTION 34-19-12, BUT THE POSITION WAS **NOT MONUMENTED** ON THIS SURVEY.  
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,640.01' WEST TO THE 1/2" REBAR OF "UNCERTAIN ORIGIN" HE FOUND AT THE NORTHWEST CORNER OF SECTION 34-19-12
  - 2) 2,640.02' EAST TO THE 1/2" SQUARE REBAR OF "UNCERTAIN ORIGIN" HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-19-12
  - 3) 2,645.52' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE CENTER OF SECTION 34-19-12
  - 4) 3,982.00' SOUTH TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE SE1/4 OF THE SW1/4 OF SECTION 34-19-12
  - 5) 5,309.47' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTH 1/4 CORNER OF SECTION 34-19-12 ON THE TOWNSHIP LINE
  - 6) SURVEY COORDINATES: N: 7309.457 E: 4645.026
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 1, 2000, FOR PROJECT NUMBER 99012-02, SURVEY F27001 IN THE SURVEY FILE FOR TOWNSHIP 19-12 TO MONUMENT THE WEST HALF OF THE NORTHWEST QUARTER OF THE NORTHWEST QUARTER OF

SECTION 27-19-12 LYING SOUTH OF THE OLD M. K. & T. RAILWAY NOW ABANDONED, SAID THAT HE DETERMINED THAT THE SOUTH 1/4 CORNER OF SECTION 27-19-12 FALLS IN CULTIVATION. HE SAID THAT IT WAS NOT FOUND ON A PRIOR SURVEY. HE DEEMED THAT THIS CORNER WAS **LOST**, AND THAT HE DID **NOT MONUMENT** THIS CORNER AT THIS TIME. HE DETERMINED A **THEORETICAL POSITION** FOR THE SOUTH 1/4 CORNER OF SECTION 27-19-12 TO BE ON LINE AND HALFWAY BETWEEN THE SOUTHWEST AND SOUTHEAST CORNERS OF SECTION 27-19-12. HE NOTED IN HIS *SURVEY NOTES*: "THIS AREA AND THIS SECTION IN PARTICULAR [SECTION 27] HAS KNOWN GLO FRAUD AS EVIDENCED BY PREVIOUS SURVEYS."

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 2,640.01' WEST TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-19-12
- 2) 2,640.01' EAST TO THE 1/2" REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 27-19-12
- 3) 2,655.51' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE CENTER CORNER OF SECTION 27-19-12
- 4) 3,984.30' NORTH TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE SE1/4 OF THE NW1/4 OF SECTION 27-19-12
- 5) 5,313.09' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 27-19-12

NORTH QUARTER CORNER 34-19-12