

WEST 1/4 CORNER SECTION 34, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ON PAGE 523 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 23" X 10" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 33 & 34-19-12.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 19 RECORDED IN SURVEY BOOK "A" ON PAGE 116 DATED FEBRUARY 25, 1868 FOR A SURVEY FOR T. MARTIN & J. ROBINSON TO ESTABLISH THE CENTER OF SECTION 33-19-12, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 33-19-12 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 319 RODS, 4 LINKS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 33-19-12
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 25 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 80 DATED MAY 20, 1874 TO SUBDIVIDE THE SOUTHWEST 1/4 OF SECTION 34-19-12 INTO EAST AND WEST HALVES, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 34-19-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 1,316-1/2' EAST TO THE 15" X 8" X 4" STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 34-19-21
 - 2) 2,633' EAST TO THE 18" X 12" X 4" STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 34-19-12
- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "B" ON PAGE 470 FOR ROAD NUMBER 221 AND DATED JULY 1883, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 34-19-12 TO BEGIN THIS ROAD SURVEY.
- 5) IN A YELLOW FIELD BOOK LABELED "MISC. 1972-1973" IN THE VAULT IN THE COUNTY ENGINEERS OFFICE ON PAGE 27 FOR A RANDOM LINE FROM THE EAST 1/4 CORNER OF SECTION 33-19-12 TO THE NORTHEAST CORNER OF SECTION 28-19-12 ON MAY 9, 1972, SAID THAT THEY BEGAN THIS SURVEY AT THE EAST 1/4 CORNER OF SECTION 33-19-12 AND RAN NORTH 7,962 FEET TO THE NORTHEAST CORNER OF SECTION 27-19-12. THEY DO **NOT** DESCRIBE THE "**MONUMENT**" AT THE EAST 1/4 CORNER OF SECTION 33-19-12, AND THERE ARE NO TIES ON THE PAGE OR IN THE SURVEY TIE FILES.
THE SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,654' NORTH TO THE IRON PIN THEY SET FOR THE SOUTHWEST CORNER OF SECTION 27-19-13, WITH A SPIKE IN A POWER POLE AT 58' NE OF THE IRON PIN SE
 - 2) 5,308' NORTH TO THE WEST 1/4 CORNER OF SECTION 27-19-12 – NOT IDENTIFIED
 - 3) 7,962' NORTH TO THE NORTHWEST CORNER OF SECTION 27-19-12 – NOT IDENTIFIED
- 6) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F27005 IN THE SURVEY FILE FOR TOWNSHIP 19-12 TO LOCATE THE LOST 1/4 CORNER BETWEEN SECTIONS 27 & 28-19-12 DATED MAY 11, 1972 SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE IN PLACE** AT THE WEST 1/4 CORNER OF SECTION 34-19-12. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 2,654' NORTH TO THE 1/2" DIAMETER REBAR HE SET FOR THE SOUTHWEST CORNER OF SECTION 27-19-12
 - 2) 5,308' NORTH TO THE 1/2" DIAMETER REBAR HE SET FOR THE WEST 1/4 CORNER OF SECTION 27-19-12
 - 3) 7,962' NORTH TO THE STONE HE FOUND "IN PLACE" AT THE NORTHWEST CORNER OF SECTION 27-19-12
- 7) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED MAY 26, 1983, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 19-12 TO LOCATE THE SOUTH 1/4 CORNER, THE EAST 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 33-19-12, SAID THAT **HE FOUND THE 3" X 10" GLO LIMESTONE** AT THE EAST 1/4 CORNER OF SECTION 33-19-12. **HE PLACED A #5 REBAR WITH A LYON COUNTY CAP ON THE WEST SIDE AND A #5 REBAR WITH A LYON COUNTY CAP ANGLED OVER THE CENTER OF THE STONE.**
- 1) A 5 REBAR WITH A LYON COUNTY CAP IS ON THE WEST SIDE OF THE STONE
 - 2) A 5 REBAR WITH A LYON COUNTY CAP IS ANGLED OVER THE CENTER OF THE STONE
 - 3) 20.0' WEST TO A LINE OF HEDGE TO THE NORTH
 - 4) 24.0' EAST TO A LINE OF POWER POLES NORTH-SOUTH
 - 5) 55.1' NE TO A SPIKE & WASHER IN A POWER POLE
 - 6) IN LINE WITH A HEDGE ROW EAST AND WEST EXTENDED
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,654.0' NORTH TO THE #4 REBAR HE FOUND AT THE NORTHEAST CORNER OF SECTION 33-19-12
 - 2) 2,654.94' SOUTH TO THE #5 REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 33-19-12 ON THE TOWNSHIP LINE
- 8) GREGORY ALAN MILES, L.S. 667, IN SURVEY F33001 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR THE SURVEY OF A 21.03 ACRE TRACT IN THE SOUTHEAST QUARTER OF THE SOUTHEAST QUARTER OF SECTION 33-19-12 FOR THE CUMMINGS PROPERTY FOR PROJECT NUMBER 83-173 DATED JUNE 3, 1983, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE 1/2" IRON PIN OVER THE STONE** AT THE EAST 1/4 CORNER OF SECTION 33-19-12. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,632.54' SOUTH TO THE 1/2" REBAR WITH HIS "LS 667" CAP HE SET FOR THE NORTHEAST CORNER OF THE 21.03 ACRE TRACT
 - 2) 2,382.69' SOUTH TO THE 1/2" REBAR WITH HIS "LS 667" CAP HE SET FOR THE SOUTHEAST CORNER OF THE 21.03 ACRE TRACT
 - 3) 2,654.94' SOUTH TO THE #5 REBAR "RECOVERED FROM COUNTY TIES" HE FOUND AT THE SOUTHEAST CORNER OF SECTION 33-19-12 ON THE TOWNSHIP LINE
- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 14, 1988, FOR PROJECT NUMBER 88219, SURVEY F34002 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR A 57.3 ACRE TRACT IN THE NORTH HALF OF THE SOUTHWEST QUARTER OF SECTION 34-19-12, SAID THAT **HE FOUND THE GLO STONE WITH A 5/8" REBAR WITH A LYON COUNTY CAP ON THE EAST SIDE OF THE STONE** AT THE WEST 1/4 CORNER OF SECTION 34-19-12 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE.
- 1) 55.4' NNE TO A PK NAIL & WASHER IN A POWER POLE
 - 2) 42.8' EAST TO A PK NAIL & WASHER IN A DOUBLE HACKBERRY TREE
 - 3) 47.4' WNW TO A PK NAIL & WASHER IN THE SOUTH TRUNK OF A TWIN HEDGE
 - 4) IN LINE WITH A HEDGE ROW TO THE EAST

HIS TIES ARE CONTINUED ON PAGE 3

- 5) 1' EAST TO THE CENTER OF THE TRAVELED WAY OF THE ROAD NORTH-SOUTH
- 6) SURVEY COORDINATES: N: 4654.9333 E: 1999.646

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,654.09' NORTH TO THE 1/2" REBAR OF "UNCERTAIN ORIGIN" HE FOUND AT THE NORTHWEST CORNER OF SECTION 34-19-12
- 2) 1,327.47' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE N1/2 OF THE SW1/4 OF SECTION 34-19-12
- 3) 2,654.93' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF SECTION 34-19-12 ON THE TOWNSHIP LINE
- 4) 2,641.37' EAST TO THE 1/2" REBAR WITH HIS "BROSEMER LS 752" CAP HE SET FOR THE CENTER CORNER OF SECTION 34-19-12
- 5) 5,279.70' EAST TO THE PK NAIL & WASHER HE SET IN THE GRAVEL ROAD SURFACE OVER A RCB FOR THE EAST 1/4 CORNER OF SECTION 34-19-12

- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F34003 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR A SURVEY OF THE SOUTH 660 FEET OF THE WEST 660 FEET OF THE SOUTHEAST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 34-19-12 FOR PROJECT NUMBER 03203-02 DATED MAY 28, 2003, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE OF RECORD WITH A 5/8" WITH A LYON COUNTY CAP ON THE EAST SIDE OF THE STONE** AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 34-19-12. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,320.68' EAST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE NE1/4 OF THE SW1/4 OF SECTION 34-19-12
- 2) 2,641.37' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP MONUMENTED ON A PRIOR SURVEY BUT NOT RECOVERED ON THIS SURVEY AT THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 34-19-12
- 3) 1,327.46' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP MONUMENTED ON A PRIOR SURVEY BUT NOT RECOVERED ON THIS SURVEY AT THE NORTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 34-19-12
- 4) 2,654.93' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND IN A MONUMENT WELL AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 34-19-12 ON THE TOWNSHIP LINE

- 11) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 19, 2010 FOR PROJECT NUMBER 10258-02, SURVEY F34004 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR THE SURVEY OF A 20 ACRE TRACT IN THE SOUTHEAST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 34-19-12 FOR MIKE ARNDT, SAID THAT **HE FOUND THE 5/8" REBAR WITH A LYON COUNTY CAP OVER THE STONE** AT THE WEST 1/4 CORNER OF SECTION 34-19-12 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE DATED OCTOBER 1988.

- 1) 55.4' NNE TO A PK NAIL & WASHER IN A POWER POLE
- 2) IN LINE WITH A HEDGE ROW TO THE EAST
- 3) 1.0' EAST TO THE CENTERLINE TRAVELED WAY OF ROAD "S" NORTH-SOUTH
- 4) 43.0' EAST TO A PK NAIL & WASHER IN A DOUBLE HACKBERRY TREE
- 5) 47.4' WNW TO A PK NAIL & WASHER IN THE SOUTH TRUNK OF A TWIN HEDGE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,320.68' EAST TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE NE1/4 OF THE SW1/4 OF SECTION 34-19-12
- 2) 2,641.37' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET ON A PREVIOUS SURVEY AT THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 34-19-12

HIS INFORMATION IS CONTINUED ON PAGE 4

- 3) 1,337.46' SOUTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 34-19-12
- 4) 2,654.93' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND IN A MONUMENT WELL AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 34-19-12 ON THE TOWNSHIP LINE

WEST QUARTER CORNER 34-19-12