

NORTH 1/4 CORNER SECTION 35, TOWNSHIP 19 SOUTH, RANGE 12 EAST

- 1) ON PAGE 514 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 15" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 35-19-12.
THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 39.77 CHAINS WEST TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-19-12
 - 2) 39.77 CHAINS EAST TO THE 36" X 9" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-19-12

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 106 RECORDED IN SURVEY BOOK "A" ON PAGE 197 DATED APRIL 7 & 8, 1869 FOR A SURVEY OF SECTION 26-19-10, SAID THAT THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 26-19-12 WAS **LOST. HE SET A STONE** FOR THE SOUTH 1/4 CORNER OF SECTION 26-19-12 EQUIDISTANT BETWEEN THE STONES THAT HE FOUND AT THE SOUTHWEST AND SOUTHEAST CORNERS OF SECTION 26-19-12 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 159 RODS, 3 LINKS WEST TO THE HE STONE FOUND AT THE SOUTHWEST CORNER OF SECTION 26-19-12
 - 2) 159 RODS, 3 LINKS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 26-19-12
 - 3) 319 RODS, 12 LINKS NORTH TO THE STONE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 26-19-12

- 3) JOHN E. TAYLOR, L.S. 713, OF TAYLOR SURVEYING CORPORATION, P.A., IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 1996, LARGE SURVEY SR#35001 IN THE SURVEY DRAWER FOR TOWNSHIP 19-12, DATED FEBRUARY 21, 1996, FOR JOB NUMBER 8446, SAID THAT HE DUG FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 35-19-12 WITH A COUNTY BACKHOE, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **LOST. HE SET A 1/2" X 24" REBAR** FOR THE NORTH 1/4 CORNER OF SECTION 35-19-12 ON LINE AND HALFWAY BETWEEN THE NORTHWEST AND NORTHEAST CORNERS OF SECTION 35-19-12.
 - 1) 42.2' SSE TO A 60 D SPIKE & SHINER IN A 10" COTTONWOOD TREE
 - 2) 49.8' SE TO A 60 D SPIKE & SHINER IN A 4" COTTONWOOD TREE
 - 3) 67.5' NW TO A 60 D SPIKE & SHINER IN A 10" MAPLE TREE
 - 4) 9.9' WNW TO A 60 D SPIKE & SHINER IN A 12" COTTONWOOD TREEHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,637.08' WEST TO THE 1/2" REBAR **HE RESET** FOR THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 35-19-12
 - 2) 2,637.08' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 35-19-12
 - 3) 2,653.27' SOUTH TO THE 1/2" REBAR HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 35-19-12
 - 4) 5,306.54' SOUTH TO THE 1/2" REBAR HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 35-19-12 ON THE TOWNSHIP LINE

NORTH QUARTER CORNER 35-19-12