

**NORTH 1/16TH CORNER NORTHEAST QUARTER SECTION 36, TOWNSHIP 19 SOUTH,
RANGE 12 EAST**

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 28 RECORDED IN SURVEY BOOK "A" ON PAGES 122 & 123 DATED MARCH 18-20, 1868 TO SURVEY J. OGDEN'S AND C. ARCHER'S LAND, BEING THE WEST 1/2 OF THE NORTHEAST 1/4, AND THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4, AND THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 36-19-12, SAID THAT **HE SET A STONE** FOR THE 1/2/4 CORNER ON THE NORTH SIDE OF THE NORTHEAST 1/4 OF SECTION 36 EQUIDISTANT BETWEEN THE STONES HE FOUND AT THE NORTH 1/4 CORNER AND THE NORTHEAST CORNER OF SECTION 36 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING DISTANCES:
 - 1) 80 RODS WEST TO THE STONE FOUND AT THE NORTH 1/4 CORNER OF SEC. 36
 - 2) 80 RODS EAST TO THE STONE FOUND AT THE NORTHEAST CORNER OF SEC. 36

- 2) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F36001 IN THE SURVEY FILE FOR TOWNSHIP 19-12 FOR A PLAT OF SURVEY TO LOCATE THE BOUNDARIES OF THE NORTHEAST 1/4 OF THE NORTHEAST 1/4 AND THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 AND THE SOUTH 5 ACRES OF THE NORTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 36-19-12 DATED APRIL 13, 1971 SHOWS ON HIS SURVEY DRAWING THAT **HE SET AN IRON PIN** FOR THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 36, BUT THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCE:
 - 1) 1,323.75' SOUTH TO AN IRON PIN SET FOR THE CENTER OF THE NE1/4 OF SEC. 36

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 36-19-12