

**WEST 1/4 CORNER SECTION 36, TOWNSHIP 19 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 509 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 11" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 35 & 36-19-12.
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 28 RECORDED IN SURVEY BOOK "A" ON PAGES 122 & 123 DATED MARCH 18-20, 1868 TO SURVEY J. OGDEN'S AND C. ARCHER'S LAND, BEING THE WEST 1/2 OF THE NORTHEAST 1/4, AND THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4, AND THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 36-19-12, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 36-19-12 ON THIS SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 319 RODS, 15 LINKS EAST TO THE STONE FOUND AT THE EAST 1/4 CORNER OF SECTION 36-19-12 ON THE RANGE LINE
- 3) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 78  
ON MAY 21, 1951 A PETITION SIGNED BY J. C. SCHUBERT FOR THE **VACATION** OF A ROAD IN TOWNSHIP 19-12 WAS PRESENTED TO GEORGE K. JACKSON, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS AND R. W. BALL, COUNTY ENGINEER, ON JUNE 12, 1951 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON JUNE 12, 1951 **VACATED** THE FOLLOWING ROAD:
  - 1) BEGINNING ON THE SOUTHEAST CORNER OF SECTION 35-19-12, THENCE NORTH TO THE QUARTER CORNER ON THE EAST LINE OF SECTION 35-19-12, A DISTANCE OF 1/2 MILE, AND THERE ENDING.
- 4) JOHN E. TAYLOR, L.S. 713, OF TAYLOR SURVEYING CORPORATION, P.A., IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 21, 1996, FOR JOB NUMBER 8446, LARGE SURVEY SR#35001 IN THE SURVEY DRAWER FOR TOWNSHIP 19-12, SAID THAT HE SEARCHED FOR THE STONE AT THE EAST 1/4 CORNER OF SECTION 35-19-12, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **LOST**. **HE SET A 1/2" IRON BAR WITH HIS "LS 713" CAP** FOR THE EAST 1/4 CORNER OF SECTION 35-19-12 ON LINE AND HALF-WAY BETWEEN THE EXISTING NORTHEAST CORNER AND SOUTHEAST CORNER OF SECTION 35-19-12.
  - 1) CORNER IS AT THE INTERSECTION OF DRAINAGE DITCHES FROM THE E-W-S
  - 2) NO OTHER REFERENCES AVAILABLEHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,651.63' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 35-19-12
  - 2) 2651.63' SOUTH TO AN IRON PIN HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 35-19-12 ON THE TOWNSHIP LINE
  - 3) 2,637.91' WEST TO THE 1/2" REBAR WITH HIS CAP HE SET FOR THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 35-19-12
  - 4) 5,275.82' WEST TO THE RAILROAD BOLT HE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 35-19-12

WEST QUARTER CORNER 36-19-12