

**CENTER CORNER OF NORTHEAST QUARTER OF SECTION 03, TOWNSHIP 19 SOUTH,  
RANGE 13 EAST**

1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED JUNE 19, 2008 FOR PROJECT NUMBER 08164-02, SURVEY F03004 IN THE SURVEY FILE FOR TOWNSHIP 19-13 FOR TWO TRACTS IN THE NORTH HALF OF THE NORTHWEST AND NORTHEAST QUARTERS OF SECTION 3-19-13 FOR WANDA STATTLER, SAID THAT **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE CENTER CORNER OF THE NORTHEAST 1/4 OF SECTION 3-19-13 ON TRUE LINE AND AT HALF THE DISTANCE BETWEEN THE EAST 1/16<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 AND THE EAST 1/16<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 3-19-13. THIS CORNER IS ALSO THE SOUTHEAST CORNER OF TRACT 2.

- 1) 3.0' NORTH TO A LINE OF FENCE TO THE EAST AND WEST
- 2) 3.00' EAST TO A LINE OF FENCE TO THE NORTH EXTENDED
- 3) 7.30' WEST TO A LINE OF FENCE TO THE SOUTH
- 4) 8.80' WEST TO A 40 D NAIL & WASHER IN AN 8" HACKBERRY TREE
- 5) 3.80' NNW TO A BOLT IN THE SOUTH FENCE CORNER POST
- 6) 12.50' NE TO A BOLT IN THE SW FACE OF A BRACE POST

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,318.07' EAST TO THE 1/2" REBAR HE FOUND AT THE EAST 1/16<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 3-19-13
- 2) 1,318.07' WEST TO THE STONE THAT SET BY RICE IN 1882 IN SURVEY BOOK "D" ON PAGE 132 HE FOUND AT THE EAST 1/16<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 3, AKA NORTHWEST CORNER OF LOT 1 OF THE NE1/4 OF SECTION 3-19-13
- 3) 3,956.84' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 3-19-13
- 4) 1,335.95' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH 1/16<sup>TH</sup> CORNER OF THE NE1/4 OF SECTION 3-19-13 ON THE TOWNSHIP LINE

CENTER CORNER NORTHEAST QUARTER 03-19-13