

**NORTH 1/4 CORNER SECTION 05, TOWNSHIP 19 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 90 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 11" X 3"** FOR THE NORTH 1/4 CORNER OF SECTION 5-19-13 ON THE NORTH TOWNSHIP BOUNDARY ON DECEMBER 27, 1855.

THE GOVERNMENT SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE NORTH TOWNSHIP BOUNDARY TO THE 24" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-19-13
  - 2) 40.00 CHAINS EAST ON THE NORTH TOWNSHIP BOUNDARY TO THE 20" X 11" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-19-13
- 2) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 22, 2016, FOR PROJECT NUMBER 16160-02, THE SURVEY OF TWO TRACTS IN THE SOUTHEAST AND SOUTHWEST QUARTERS OF SECTION 5-19-13 FOR JOAN AND BRIAN GOURLEY AT 1845 COUNTY ROAD "X", SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 19-13, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE OF RECORD AT THE NORTH 1/4 CORNER OF SECTION 5-19-13 ON THE COUNTY LINE, BUT THE STONE WAS **NOT** FOUND. HE DEEMED THAT THIS CORNER WAS **LOST** IN NORTH-SOUTH POSITION AND **OBLITERATED** IN EAST-WEST POSITION. **HE RESET** THIS CORNER ON THE TOWNSHIP LINE BETWEEN THE NORTHEAST CORNER AND THE NORTHEAST CORNER OF SECTION 5-19-13.

- 1) 7.00' SOUTH T THE CENTERLINE OF COUNTY ROAD 190 EAST-WEST
- 2) 21.50' NW TO A CONCRETE NAIL & BOTTLECAP IN A BRACE POST
- 3) 21.60' NORTH TO A CONCRETE NAIL & BOTTLECAP IN THE WEST GATE POST
- 4) 31.80' NE TO A CONCRETE NAIL & BOTTLECAP IN THE EAST GATE POST
- 5) 30.00' WEST TO A LINE OF FENCE TO THE SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,671.01' WEST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND FROM REFERENCE TIES AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 5-19-13
- 2) 2,631.95' EAST ON THE TOWNSHIP LINE TO THE #5 SQUARE IRON BAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 5-19-13
- 3) 2,631.36' SOUTH TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 5-19-13, BEING THE NORTHWEST CORNER OF TRACT C AND THE NORTHEAST CORNER OF THE WEST 33 FEET OF THE SW1/4 OF SECTION 5-19-13
- 4) 3,952.48' SOUTH TO THE 1/2" X 24" REBAR WITH HIS "PS 752" CAP HE SET FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE SE1/4 OF SECTION 5-19-13
- 5) 5,273.60' SOUTH TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 5-19-13, BEING THE POINT OF BEGINNING OF TRACT C AND THE SOUTHEAST CORNER OF THE WEST 33 FEET OF THE SW1/4 OF SECTION 5-19-13

NORTH QUARTER CORNER 05-19-13