

WEST 1/4 CORNER SECTION 05, TOWNSHIP 19 SOUTH, RANGE 13 EAST

- 1) ON PAGE 667 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 6-19-13 ON OCTOBER 20, 1860. THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.70 CHAINS NORTH TO THE 24" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-19-13 ON THE NORTH TOWNSHIP BOUNDARY
 - 2) 40.00 CHAINS SOUTH TO THE 24" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-19-13

- 2) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JULY 22, 2016, FOR PROJECT NUMBER 16160-02, THE SURVEY OF TWO TRACTS IN THE SOUTHEAST AND SOUTHWEST QUARTERS OF SECTION 5-19-13 FOR JOAN AND BRIAN GOURLEY AT 1845 COUNTY ROAD "X", SURVEY F05001 IN THE SURVEY FILE FOR TOWNSHIP 19-13, SAID THAT HE LOOKED FOR THE STONE OF RECORD AT THE WEST 1/4 CORNER OF SECTION 5-19-13 BUT HE DID **NOT** FIND THE STONE. HE DEEMED THAT THIS CORNER WAS **OBLITERATED** AND **HE RESET** THIS CORNER ON THE NORTH SIDE OF A CORNER FENCE POST FOR A FENCE TO THE SOUTH. **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE WEST 1/4 CORNER OF SECTION 5-19-13.
 - 1) 0.60' SOUTH TO A LINE OF FENCE RUNNING EAST AND WEST
 - 2) 0.50' WEST TO A LINE OF FENCE RUNNING SOUTH
 - 3) 26.00' EAST TO A LINE OF FENCE RUNNING NORTH
 - 4) 7.20' NW TO A CONCRETE NAIL & BOTTLECAP IN A WOOD POST
 - 5) 0.50' SW TO THE NEAR FACE OF A PIPE COUNTY FENCE POSTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,620.73' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND FROM REFERENCE TIES AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 5-19-13 ON THE TOWNSHIP LINE
 - 2) 2,638.90' SOUTH TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 5-19-13
 - 3) 2,621.62' EAST TO THE 1/2" X 24" REBAR WITH HIS "PS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE EAST 33 FEET OF THE SW1/4 OF SECTION 5-19-13
 - 4) 2,654.62' EAST TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 5-19-13, BEING THE NORTHEAST CORNER OF THE EAST 33 FEET OF THE SW1/4 OF SECTION 5-19-13 AND THE NORTHWEST CORNER OF TRACT C
 - 5) 3,578.62' EAST TO THE 1/2" X 24" REBAR WITH HIS "PS 752" CAP HE SET FOR THE NORTHEAST CORNER OF TRACT C AND THE NORTHWEST CORNER OF TRACT B
 - 6) 4,652.50' EAST TO THE 1/2" X 24" REBAR WITH HIS "PS 752" CAP HE SET FOR THE NORTH CORNER OF TRACT B, BEING THE NORTHEAST CORNER OF TRACT C AND THE NORTHWEST CORNER OF TRACT A PREVIOUSLY SURVEYED IN 2016
 - 7) 5,292.50' EAST TO THE 5/8" SQUARE IRON PIN FROM AI CHAMNESS IN 1939 HE FOUND AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 5-19-13, AND THE NORTHEAST CORNER OF TRACT A PREVIOUSLY SURVEYED IN 2016

- 3) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F05002 IN THE SURVEY FILE FOR TOWNSHIP 19-13 DATED SEPTEMBER 1, 2016 FOR HIS PROJECT NUMBER 16160-02 FOR THE SURVEY OF AN 8.88 ACRE TRACT IN THE NORTHEAST CORNER OF THE SOUTHEAST QUARTER OF SECTION 5-19-13 FOR JOAN AND BRIAN GOURLEY, SHOWS ON HIS REPORT OF SURVEY THAT **HE SET A 5/8" X 24" REBAR WITH A LYON COUNTY CAP** FOR THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 5-19-13. **[NOTE:** HE HAD SET THIS 5/8" REBAR WITH A LYON COUNTY CAP ON JULY 22, 2016 FOR ANOTHER SURVEY FOR GOURLEY AND HIS

TIES FROM JULY ARE STILL VALID AND ARE NOT DUPLICATED. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 4,652.49' EAST TO THE 1/2" X 24" REBAR WITH HIS "752" CAP HE SET FOR THE NORTHWEST CORNER OF THE 8.88 ACRE TRACT
- 2) 5,292.49' EAST TO THE SQUARE 5/8" IRON PIN FOUND FROM CHAMNESS IN 1939 AT THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 5-19-12

WEST QUARTER CORNER 05-19-13