

**CENTER CORNER SECTION 15, TOWNSHIP 19 SOUTH, RANGE 13 EAST**

- 1) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGES 15 & 16 FOR LYMAN FRY, W. R. & C. H. COLE, JAMES A. ALLER, WILLIAM A. JONES, OTTO J. JOHNSON, E. T. WHITE, JESSIE FLEMING, C. B. HILL, JAMES C. GAMBLE, AND HENRY JACOB REQUESTING A SURVEY TO PERMANENTLY ESTABLISH THE CORNERS AND BOUNDARIES OF THE FOLLOWING DESCRIBED LANDS: NORTHEAST 1/4 OF SECTION 27; SOUTHEAST 1/4, NORTHEAST 1/4, & WEST 1/2 OF NORTHEAST 1/4 OF SECTION 22; WEST 1/2 & SOUTHEAST 1/4 OF THE NORTHEAST 1/4 AND THE NORTHEAST 1/4 OF THE NORTHEAST 1/4, EAST 1/2 OF NORTHWEST 1/4 & NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 15; THE EAST 1/2 AND SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 AND THE SOUTH 1/2 OF THE NORTHEAST 1/4 LYING SOUTH OF THE INDIAN RESERVATION IN SECTION 10; THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 3, ALL IN TOWNSHIP 19, RANGE 13, SAID THAT **HE SET A 20" X 7" X 7" LIMESTONE MARKED WITH A "+" ON TH TOP** FOR THE PERMANENT CENTER CORNER OF SECTION 15-19-13 ON THIS **PERMANENT SURVEY**. THE SURVEY BEGAN APRIL 30 AND WAS COMPLETED AUGUST 9, 1894, AND WAS FILED ON AUGUST 27, 1984.
  
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED MAY 1, 2007, FOR PROJECT NUMBER 07122-02, SURVEY F15002 IN THE SURVEY FILE FOR TOWNSHIP 19-13 FOR A 10.0 ACRE TRACT LOCATED IN THE NORTHWEST QUARTER AND A 0.83 ACRE TRACT IN THE NORTHEAST QUARTER OF SECTION 15-19-13 FOR HOGAN, SAID THAT **HE FOUND A 7" X 4" LIMESTONE** AT THE CENTER CORNER OF SECTION 15-19-13 FROM A PERMANENT SURVEY BY MATTHEW BROWN RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 15, DATED 1894.
  - 1) 5/8" X 24" REBAR WITH A LYON COUNTY CAP SET ON THE NORTH SIDE AND FLUSH WITH THE TOP CENTER OF THE LIMESTONE
  - 2) 1/2" X 24" REBAR WITH HIS "LS 752" CAP SET ON THE SOUTH SIDE AND FLUSH WITH THE TOP CENTER OF THE LIMESTONE
  - 3) 1.0' EAST TO A LINE OF FENCE NORTH-SOUTH
  - 4) 7.5' SOUTH TO A LINE OF FENCE EAST-WEST
  - 5) 7.7' SOUTH TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
  - 6) 10.05' SW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

  - 1) 1,863.01' NORTH TO THE SOUTHEAST CORNER OF THE 10.0 ACRE TRACT AND THE SOUTHWEST CORNER OF THE 0.83 ACRE TRACT
  - 2) 2,610.08' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET ON THE SOUTH RIGHT-OF-WAY LINE OF COUNTY ROAD 170, AND THE P.O.B. OF THE 10.0 ACRE TRACT AND THE P.O.B. OF THE 0.83 ACRE TRACT
  - 3) 2,643.08' NORTH TO A MAG NAIL IN THE CONCRETE PAVEMENT HE SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 15-19-13
  - 4) 2,642.88' SOUTH TO A 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 15-19-13

CENTER CORNER OF 15-19-13