

WEST 1/4 CORNER SECTION 15, TOWNSHIP 19 SOUTH, RANGE 13 EAST

1) ON PAGE 653 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 15 & 16-19-13.

2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGES 15 & 16 FOR LYMAN FRY, W. R. & C. H. COLE, JAMES A. ALLER, WILLIAM A. JONES, OTTO J. JOHNSON, E. T. WHITE, JESSIE FLEMING, C. B. HILL, JAMES C. GAMBLE, AND HENRY JACOB REQUESTING A SURVEY TO PERMANENTLY ESTABLISH THE CORNERS AND BOUNDARIES OF THE FOLLOWING DESCRIBED LANDS: NORTHEAST 1/4 OF SECTION 27; SOUTHEAST 1/4, NORTHEAST 1/4, & WEST 1/2 OF NORTHEAST 1/4 OF SECTION 22; WEST 1/2 & SOUTHEAST 1/4 OF THE NORTHEAST 1/4 AND THE NORTHEAST 1/4 OF THE NORTHEAST 1/4, EAST 1/2 OF NORTHWEST 1/4 & NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 15; THE EAST 1/2 AND SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 AND THE SOUTH 1/2 OF THE NORTHEAST 1/4 LYING SOUTH OF THE INDIAN RESERVATION IN SECTION 10; THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 3, ALL IN TOWNSHIP 19, RANGE 13, SAID THAT **HE SET A 21" X 10" X 3" LIMESTONE" MARKED "1/4" ON THE WEST SIDE** FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 15-19-13 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 15-19-13 AND THE STONE THAT HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 15-19-13 ON THIS **PERMANENT SURVEY**. THE SURVEY BEGAN APRIL 30 AND WAS COMPLETED AUGUST 9, 1894, AND WAS FILED ON AUGUST 27, 1984.

HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.02-4/10 CHAINS NORTH TO THE 22" X 12" X 3" LIMESTONE MARKED "1/8" ON THE WEST SIDE HE SET FOR THE PERMANENT WEST 1/8TH CORNER OF THE NW1/4 OF SECTION 15-19-13
- 2) 40.04-8/10 CHAINS NORTH TO THE 16" X 12" X 6" LIMESTONE "MARKED ACCORDING TO REGULATIONS" HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 15-19-13
- 3) 40.04-8/10 CHAINS SOUTH TO THE 25" X 11" X 4-1/2" LIMESTONE "MARKED ACCORDING TO GOVERNMENT REGULATIONS" HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 15-19-13

3) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F16001 IN THE SURVEY FILE FOR TOWNSHIP 19-13 TO LOCATE THE LINES OF THE SOUTH HALF AND THE NORTH HALF OF THE NORTH HALF OF THE SOUTH HALF OF THE EAST HALF OF THE SOUTH HALF OF THE NORTHEAST QUARTER OF SECTION 16-19-12 DATED MAY 11, 1971, SHOWS ON HIS SURVEY DRAWING THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE EAST 1/4 CORNER OF SECTION 16-19-13 TO BE ON LINE AND HALFWAY BETWEEN THE PIN IN PAVEMENT HE FOUND AT THE NORTHEAST CORNER OF SECTION 16-19-13 AND THE STONE HE FOUND IN PLACE AT THE SOUTHEAST CORNER OF SECTION 16-19-13.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 330.6' NORTH TO THE IRON PIN HE SET FOR THE SOUTHEAST CORNER OF THE LAMBETH TRACT
- 2) 459.9' NORTH TO THE IRON PIN HE SET FOR THE NORTHEAST CORNER OF THE LAMBETH TRACT
- 3) 661.2' NORTH TO THE IRON PIN SET FOR THE NORTHEAST CORNER OF THE STOCKWELL TRACT
- 4) 1,322.5' NORTH TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE SE1/4 OF THE NE1/4 OF SECTION 16-19-13

HIS INFORMATION IS CONTINUED ON PAGE 2

- 5) 2,645' NORTH TO THE PIN IN PAVEMENT HE FOUND AT THE NORTHEAST CORNER OF SECTION 16-19-13
 - 6) 2,645' SOUTH TO THE STONE HE FOUND IN PLACE AT THE SOUTHEAST CORNER OF SECTION 16-19-13
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 13, 2005, FOR PROJECT NUMBER 05407-02, SAID THAT HE CONSIDERED THAT THE EAST 1/4 CORNER OF SECTION 16-19-13 WAS **LOST. HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE EAST 1/4 CORNER OF SECTION 16-19-13 ON TRUE LINE AND AT HALF THE DISTANCE BETWEEN THE SOUTHEAST AND NORTHEAST CORNERS OF SECTION 16-19-13.
 - 1) THIS CORNER FALLS IN THE BACKSLOPE OF THE WEST DITCH OF COUNTY ROAD "Y"
 - 2) 54.15' ESE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 3) 27.20' SOUTH TO A 40 D NAIL & WASHER IN A POWER POLE
 - 4) 17.5' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "Y"
 - 5) 13.0' SOUTH TO A LINE OF FENCE TO THE EAST EXTENDED
 - 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 22, 2008 FOR PROJECT NUMBER 08241-02, SURVEY F16002 IN THE SURVEY FILE FOR TOWNSHIP 19-13 TO SURVEY THE SOUTH HALF OF THE NORTHEAST QUARTER OF SECTION 16-19-13 EXCEPT THE SOUTH 1/2 OF THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SAID SECTION 16 FOR STEPHEN STOCKWELL, SAID THAT **HE FOUND THE 1/2" X 24 REBAR WITH HIS "LS 752" CAP** AT THE EAST 1/4 CORNER OF SECTION 16-19-13 FROM HIS EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.
 - 1) THIS CORNER FALLS ON THE BACKSLOPE OF THE WEST DITCH OF COUNTY ROAD "Y"
 - 2) 17.5' EAST TO THE CENTERLINE TRAVELED WAY FOR COUNTY ROAD "Y"
 - 3) 54.15' ESE TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 4) 27.20' SOUTH TO A 40 D NAIL & WASHER IN A POWER POLE
 - 5) 13.0' SOUTH TO A LINE OF FENCE TO THE EAST EXTENDED

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 661.09' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE N1/2 OF THE SE1/4 OF THE NE1/4 OF SEC. 16-19-13
 - 2) 1,322.18' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 16-19-13
 - 3) 2,644.35' NORTH TO THE 1-3/4" IRON PIN HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 16-19-13
 - 4) 1,309.54' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF THE NE1/4 OF SECTION 16-19-13
 - 5) 2,619.08' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 16-19-13
 - 6) 5,274.33' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 16-19-13

WEST QUARTER CORNER 15-19-13