

**WEST 1/16<sup>TH</sup> CORNER NORTHWEST QUARTER OF SECTION 15, TOWNSHIP 19 SOUTH,  
RANGE 13 EAST**

- 1) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGES 15 & 16 FOR LYMAN FRY, W. R. & C. H. COLE, JAMES A. ALLER, WILLIAM A. JONES, OTTO J. JOHNSON, E. T. WHITE, JESSIE FLEMING, C. B. HILL, JAMES C. GAMBLE, AND HENRY JACOB REQUESTING A SURVEY TO PERMANENTLY ESTABLISH THE CORNERS AND BOUNDARIES OF THE FOLLOWING DESCRIBED LANDS: NORTHEAST 1/4 OF SECTION 27; SOUTHEAST 1/4, NORTHEAST 1/4, & WEST 1/2 OF NORTHEAST 1/4 OF SECTION 22; WEST 1/2 & SOUTHEAST 1/4 OF THE NORTHEAST 1/4 AND THE NORTHEAST 1/4 OF THE NORTHEAST 1/4, EAST 1/2 OF NORTHWEST 1/4 & NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 15; THE EAST 1/2 AND SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 AND THE SOUTH 1/2 OF THE NORTHEAST 1/4 LYING SOUTH OF THE INDIAN RESERVATION IN SECTION 10; THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 3, ALL IN TOWNSHIP 19, RANGE 13, SAID THAT HE SET A 22" X 12" X 3" LIMESTONE MARKED "1/8" ON THE WEST SIDE FOR THE PERMANENT WEST 1/8<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 5-19-13 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 15-19-13 AND THE STONE THAT HE SET FOR THE PERMANENT WEST 1/4 CORNER OF SECTION 15-19-13 ON THIS **PERMANENT SURVEY**. THE SURVEY BEGAN APRIL 30 AND WAS COMPLETED AUGUST 9, 1894, AND WAS FILED ON AUGUST 27, 1984.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.02-4/10 CHAINS NORTH TO THE 16" X 12" X 6" LIMESTONE "MARKED ACCORDING TO GOVERNMENT REGULATIONS" HE SET FOR THE NORTHWEST CORNER OF SECTION 15-19-13
  - 2) 20.02-4/10 CHAINS SOUTH TO THE 21" X 10" X 3" LIMESTONE MARKED "1/4" ON THE WEST SIDE HE SET FOR THE WEST 1/4 CORNER OF SECTION 15-19-13
  - 3) 60.07-2/10 CHAINS SOUTH TO THE 25" X 11" X 4-1/2" LIMESTONE "MARKED ACCORDING TO GOVERNMENT REGULATIONS" HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 15-19-13
- 2) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F16001 IN THE SURVEY FILE FOR TOWNSHIP 19-13 TO LOCATE THE LINES OF THE SOUTH HALF AND THE NORTH HALF OF THE NORTH HALF OF THE SOUTH HALF OF THE EAST HALF OF THE SOUTH HALF OF THE NORTHEAST QUARTER OF SECTION 16-19-12 DATED MAY 11, 1971, SHOWS ON HIS SURVEY DRAWING THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 16-19-13 TO BE HALFWAY BETWEEN THE NORTHEAST CORNER OF SECTION 16-19-13 AND THE THEORETICAL POSITION FOR THE EAST 1/4 CORNER OF SECTION 16-19-13, BUT HE DID **NOT** MONUMENT THE POSITION ON THE SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,322.5' NORTH TO THE PIN IN PAVEMENT HE FOUND AT THE NORTHEAST CORNER OF SECTION 16-19-13
- 2) 661.25' SOUTH TO THE IRON PIN HE SET FOR THE NORTHEAST CORNER OF THE STOCKWELL TRACT
- 3) 826.55' SOUTH TO THE IRON PIN HE SET FOR THE NORTHEAST CORNER OF THE LAMBETH TRACT
- 4) 991.85' SOUTH TO THE IRON PIN HE SET FOR THE SOUTHEAST CORNER OF THE LAMBETH TRACT
- 5) 1,322.5' SOUTH TO THE THEORETICAL POSITION FOR THE EAST 1/4 CORNER OF SECTION 16-19-13
- 6) 3,967.5' SOUTH TO THE STONE HE FOUND IN PLACE AT THE SOUTHEAST CORNER OF SECTION 16-19-13

3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED AUGUST 22, 2008 FOR PROJECT NUMBER 08241-02, SURVEY F16002 IN THE SURVEY FILE FOR TOWNSHIP 19-13 TO SURVEY THE SOUTH HALF OF THE NORTHEAST QUARTER OF SECTION 16-19-13 EXCEPT THE SOUTH 1/2 OF THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SAID SECTION 16 FOR STEPHEN STOCKWELL, SAID THAT **HE SET A 1/2" REBAR WITH HIS "LS 752" CAP** FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE NORTHEAST 1/4 OF SECTION 16-19-13 ON TRUE LINE AND HALFWAY BETWEEN THE NORTHEAST CORNER AND THE EAST QUARTER CORNER OF SECTION 16-19-13.

- 1) 33.20' ESE TO A 40 D NAIL & BOTTLECAP IN THE WEST FACE OF A POWER POLE
- 2) 41.0' SW TO A CONCRETE NAIL & WASHER IN A 3" MAPLE TREE
- 3) 18.0' SOUTH TO THE CENTERLINE OF A DRIVEWAY TO THE WEST EXTENDED
- 4) 20.75' NNW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 5) 4.3' SOUTH TO A LINE OF POWER POLES TO THE WEST
- 6) 14.5' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "Y" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,322.17' NORTH TO THE 1-3/4" IRON PIN HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 16-19-13
- 2) 661.09' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE N1/2 OF THE SE1/4 OF THE NE1/4 OF SEC. 16-19-13
- 3) 1,322.18' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 16-19-13
- 4) 1,309.17' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE N1/2 OF THE SE1/4 OF THE NE1/4 OF SEC. 16-19-13
- 5) 2,618.34' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE SW1/4 OF THE NE1/4 OF SECTION 16-19-13

WEST SIXTEENTH CORNER NORTHWEST QUARTER 15-19-13