

**WEST 1/16TH CORNER SOUTHWEST QUARTER OF SECTION 16, TOWNSHIP 19 SOUTH,
RANGE 13 EAST**

- 1) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 146 ORDERED BY A. E. MOUNKES TO LOCATE THE NORTH LINE OF THE SOUTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 17, SAID THAT HE BEGAN THIS SURVEY AT 9:00 A.M. ON FEBRUARY 17, 1947 WITH NONE OF THE INTERESTED PARTIES BEGIN PRESENT, AND WAS CARRIED THROUGH THE DAYS OF FEBRUARY 17, 18, 19, 20 & 21, 1947 UNTIL COMPLETE. HE SAID THAT **HE SET A “MARK IN PAVING”** FOR THE PERMANENT NORTHEAST CORNER OF THE SOUTH 1/2 OF THE SOUTHEAST CORNER OF SECTION 17-19-13 ON LINE AND HALFWAY BETWEEN THE EAST 1/4 CORNER AND THE SOUTHEAST CORNER OF SECTION 16-19-13 ON THIS **PERMANENT SURVEY**.
 - 1) 36.5’ SE TO A 3/4” DIAMETER REBAR IN A HEDGEROW
 - 2) 34.2’ NE TO A 3/4” DIAMETER REBAR IN A HEDGEROW

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 3) 1,323.4’ SOUTH TO THE “MARK IN THE PAVING” HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 17-19-13 AND WITNESSED AS FOLLOWS: 32.75’ NE TO THE NW HR POLE; 37.35’ SE TO THE SW HR POLE; 57.5’ SE TO AN IRON PIN; AND 47.3’ NE TO AN IRON PIN
 - 4) 6,617.0’ SOUTH TO THE END OF THE CONCRETE PAVING AT THE SOUTHEAST CORNER OF SECTION 21-19-13 WITH NO WITNESSES LISTED
 - 5) 1,323.4’ NORTH TO THE “MARK IN THE PAVING” HE SET FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 17-19-13 AND WITNESSED AS FOLLOWS: 49.0’ NW TO A SPIKE & WASHER IN THE ROOT OF A MAPLE TREE; AND 30.0’ EAST TO AN IRON PIN NEAR A CORNER FENCE POST
 - 6) 3,970.2’ NORTH TO THE NORTHEAST CORNER OF SECTION 17-19-13 – NOT IDENTIFIED AND NO WITNESSES
- 2) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-13 SHOWS A **STONE** AT THE “SW CORNER NW1/4 SW1/4 OF SECTION 16-19-13”.
 - 1) 36.5’ [SE] TO A REBAR
 - 2) 34.2’ NE TO A REBAR

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 16-19-13