

CENTER CORNER SECTION 20, TOWNSHIP 19 SOUTH, RANGE 13 EAST

- 1) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 91 RECORDED IN SURVEY BOOK "A" ON PAGE 185 AND DATED FEBRUARY 16, 1869 FOR A SURVEY OF LAND OWNED BY H. BROWN, BEING IN SECTION 20-19-13, TO DIVIDE THE NORTHWEST 1/4 BY AN EAST AND WEST LINE, SAID THAT **HE FOUND THE STONE "ALREADY ESTABLISHED"** AT THE CENTER CORNER OF SECTION 20-19-13 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 80 RODS NORTH TO THE STONE HE SET FOR THE EAST 1/2/4 CORNER OF THE NW1/4 OF SECTION 20-19-13
 - 2) 160 RODS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 20-19-13

- 2) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A **LEGAL SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 175 THAT BEGAN APRIL 24, 1917 ORDERED BY BERT S. WHITE TO ESTABLISH THE CORNERS AND BOUNDARIES OF HIS LAND IN SECTION 20-19-13, SAID THAT **HE SET A HEDGE STAKE** FOR THE CENTER CORNER OF SECTION 20-19-13 ON LINE AND AT THE PROPER CORRECTION BETWEEN THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 20-19-13 AND THE POST HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 20-19-13 ON THIS **PERMANENT SURVEY**.

CENTER CORNER OF 20-19-13