

NORTH 1/4 CORNER SECTION 20, TOWNSHIP 19 SOUTH, RANGE 13 EAST

- 1) ON PAGE 663 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 2-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 17 & 20-19-13.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.02 CHAINS WEST TO THE 20" X 10" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-19-13
 - 2) 40.02 CHAINS EAST TO THE 16" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-19-13

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 82 RECORDED IN SURVEY BOOK "A" ON PAGES 178 AND CONTINUED AT THE BOTTOM OF PAGE 180 DATED FEBRUARY 2, 1869 FOR A SURVEY OF LAND OWNED BY G. S. STILLINGS AND OTHERS, BEING IN SECTION 17-19-13, TO ESTABLISH THE CENTER CORNER AND ALSO THE SOUTHEAST CORNER OF THE NORTH 1/2 OF THE SOUTHWEST 1/4 OF SAID SECTION 17, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 17-19-13 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 158 RODS, 7 LINKS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 17-19-13
 - 2) 159 RODS, 24 LINKS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 17-19-13

- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 91 RECORDED IN SURVEY BOOK "A" ON PAGE 185 AND DATED FEBRUARY 16, 1869 FOR A SURVEY OF LAND OWNED BY H. BROWN, BEING IN SECTION 20-19-13, TO DIVIDE THE NORTHWEST 1/4 BY AN EAST AND WEST LINE, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 20-19-13 ON THIS SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 80 RODS SOUTH TO THE STONE HE SET FOR THE EAST 1/2/4 CORNER OF THE NW1/4 OF SECTION 20-19-13
 - 2) 160 RODS SOUTH TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 20-19-13

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 3, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 3 DATED JANUARY 19, 1870 TO ESTABLISH THE CENTER CORNER OF SECTION 17-19-13, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 17-19-13 ON THIS **PERMANENT SURVEY**. HE NOTED "McAULEY'S NO. 28" ON THE LEFT PAGE.

- 5) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 175 THAT BEGAN APRIL 24, 1917 ORDERED BY BERT S. WHITE TO ESTABLISH THE CORNERS AND BOUNDARIES OF HIS LAND IN SECTION 20-19-13, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 20-19-13 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,646' WEST TO THE STONE HE SET FOR THE PERMANENT NORTHWEST CORNER OF SECTION 20-19-13
 - 2) 3,972' SOUTH TO THE POST HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE S1/2 OF THE SW1/4 OF SECTION 20-19-13

- 6) E. C. GOLDSMITH, COUNTY ENGINEER FROM 1944 TO 1949, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 146 ORDERED BY A. E. MOUNKES TO

LOCATE THE NORTH LINE OF THE SOUTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 17, SAID THAT HE BEGAN THIS SURVEY AT 9:00 A.M. ON FEBRUARY 17, 1947 WITH NONE OF THE INTERESTED PARTIES BEGIN PRESENT, AND WAS CARRIED THROUGH THE DAYS OF FEBRUARY 17, 18, 19, 20 & 21, 1947 UNTIL COMPLETE. HE SAID THAT **HE FOUND A 2" GAS PIPE DRIVEN IN THE GROUND** AT THE SOUTH 1/4 CORNER OF SECTION 17-19-13 ON THIS **PERMANENT SURVEY**. THERE ARE NO WITNESSES LISTED ON THE SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,640.6' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 17-19-13
 - 2) 1,320.5' NORTH TO THE 3/4" DIAMETER REBAR HE SET FOR THE PERMANENT NORTHWEST CORNER OF THE S1/2 OF THE SE1/4 OF SECTION 17-19-13 WITNESSED AS FOLLOWS: 28.85' EAST OF SOUTH TO A SPIKE IN A BLAZED WALNUT TREE; 26.9' SOUTHWEST TO A SPIKE IN A BLAZED WALNUT TREE; AND 16.35' NORTHEAST TO A SPIKE IN A BLAZED HACKBERRY TREE
 - 3) 2,641.0' NORTH TO THE 3/4" DIAMETER REBAR HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 17-19-13 WITNESSED AS FOLLOWS: 9.2' NORTH-EAST TO A SPIKE IN A BLAZED 15" WALNUT TREE; 8.9' NORTH OF EAST TO A CORNER FENCE POST; AND 18.0' SOUTHEAST TO A SPIKE IN A BLAZED HICKORY TREE
- 7) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-13 SHOWS A **2" GAS PIPE** AT THE "S1/4 CORNER SECTION 17-19-13", BUT THERE ARE NO TIES ON THE PAGE.

- 8) LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, IN SURVEY F17003 IN THE SURVEY FILE FOR TOWNSHIP 19-13 FOR THE SURVEY OF A 24 ACRE TRACT IN THE SOUTHWEST QUARTER OF SECTION 24-19-13 DATED JUNE 8, 1973, SHOWS ON HIS SURVEY DRAWING A "**MARK**" FOR THE SOUTH 1/4 CORNER OF SECTION 17-19-13. THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,646.0' WEST TO THE "MONUMENT" AT THE SOUTHWEST CORNER OF SECTION 17-19-13 – NOT IDENTIFIED
- 2) 1,864.66' NORTH TO THE IRON PIN HE SET FOR THE NORTHEAST CORNER OF THE 24 ACRE TRACT
- 3) 2,259.57' NORTH TO THE IRON PIN HE SET FOR THE NORTHEAST CORNER OF THE 24 ACRE TRACT
- 4) 2,641' NORTH TO THE "MONUMENT" AT THE CENTER CORNER OF SECTION 17-19-13 – NOT IDENTIFIED

- 9) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 27, 2000, FOR PROJECT NUMBER 00408-02, SURVEY F17004 IN THE SURVEY FILE FOR TOWNSHIP 19-13 FOR THREE TRACTS IN THE SOUTHWEST QUARTER OF SECTION 17-19-13, SAID THAT **HE FOUND A 1-1/2" PIPE [BENT TO THE EAST] AND PAINTED RED ON THE TOP** AT THE SOUTH 1/4 CORNER OF SECTION 17-19-13 FROM THE 1948 PERMANENT SURVEY BY KRETSINGER.

- 1) 13.0' WEST TO A 40 D SPIKE & WASHER IN A 28" ELM TREE
- 2) 9.25' EAST TO A 40 D SPIKE & WASHER IN A 24" HACKBERRY TREE
- 3) 36.45' SE TO A 40 D SPIKE & WASHER IN A 15" HACKBERRY TREE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,641.10' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 17-19-13

HIS INFORMATION IS CONTINUED ON PAGE 3

- 2) 660.00' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE N1/2 OF THE S1/2 OF THE SW1/4 OF SECTION 17-19-13, AND THE SOUTHEAST CORNER OF TRACT "C"
- 3) 1,180.74' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF TRACT "C", AND THE SOUTHEAST CORNER OF TRACT "B"
- 4) 2,258' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE NORTH 382' OF THE SW1/4 OF SECTION 17-19-13, AND THE NORTHEAST CORNER OF TRACT "B"
- 5) 2,640.00' NORTH TO THE 3/4" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE SW1/4 OF SECTION 17-19-13

NORTH QUARTER CORNER 20-19-13