

**WEST 1/4 CORNER SECTION 30, TOWNSHIP 19 SOUTH, RANGE 13 EAST**

- 1) ON PAGE 87 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 3"** FOR THE WEST 1/4 CORNER OF SECTION 30-19-13 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 24, 1855.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 24" X 12" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-19-13
  - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 22" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-19-13
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT SIDE OF PAGE 146 DATED JANUARY 19, 1876, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE NORTHWEST CORNER OF SECTION 30-19-13 ON THE RANGE LINE ON THIS ROAD SURVEY.
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 240 & 241 FOR A PETITION BY HAMILTON HOWARD AND OTHERS FOR A CHANGE IN THE "EMPORIA AND NEOSHO RAPIDS ROAD" [PACKET 189 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 19, 1876, AND WAS ESTABLISHED AS A 54 FOOT WIDE ROAD ON JULY 6, 1876, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF SECTION 30-19-13 ON THE RANGE LINE ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS NORTH ON THE RANGE LINE FOR 1,565' TO WHERE THE "EMPORIA AND NEOSHO RAPIDS ROAD" CROSSES THE WEST LINE OF THE NW/4 OF SECTION 30-19-13 TO COMMENCE THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS EAST ON THE 1/4 SECTION LINE FOR 3,102' UNTIL IT INTERSECTS THE "EMPORIA AND NEOSHO RAPIDS ROAD" FOR THE TERMINATION OF THIS ROAD SURVEY
- 4) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 19-13 SHOWS A **STONE** AT THE "W1/4 CORNER SECTION 30-19-13" ON THE RANGE LINE.
  - 1) 56.2' WEST TO A 12" ELM TREE
  - 2) 36' SW TO AN IRON PIN
  - 3) 52.1' SE TO AN IRON PIN
- 5) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 65 AT THE BOTTOM OF THE PAGE SHOWS A **STONE** AT THE "W1/4 CORNER SECTION 30-19-13" ON THE RANGE LINE.
  - 1) 56.3' WEST TO THE NEAR FACE OF A 12" ELM TREE
  - 2) 36.0' SW TO AN IRON PIN UNDER A GUY WIRE
  - 3) 52.1' SE TO AN IRON PIN UNDER A GUY WIRE
- 6) JAMES H. BROSEMER, L.S. 82, IN A SECTION CORNER REPORT DATED APRIL 1979, SURVEY F30001 IN THE SURVEY FILE FOR TOWNSHIP 19-13 FOR A TRACT IN THE NORTHEAST QUARTER OF SECTION 30-19-13 FOR ERNEST JACKSON, SAID THAT HE EXCAVATED WITH A COUNTY MOTOR GRADER FOR THE STONE AT THE WEST 1/4 CORNER OF SECTION 30-19-13 ON THE RANGE LINE. **HE FOUND A 6" X 11" X 11" WHITE LIMESTONE AT 14" DEEP. HE SET A 1/2" X 24" REBAR WITH HIS "BROSEMER LS 82" CAP BELOW THE STONE, AND HE SET AN 80 D SPIKE OVER THE STONE** AT THE WEST 1/4 CORNER OF SECTION 30-19-13.

HIS TIES ARE ON PAGE 2

- 1) **5.0' NORTH TO A 5/8" REBAR FOUND**
- 2) 24.1' WSW TO A SPIKE & WASHER IN A POWER POLE
- 3) 36.2' SW TO A 3/4" REBAR
- 4) 34.1' SW TO A SPIKE & WASHER IN AN 8" ELM TREE
- 5) 3.0' EAST TO THE CENTERLINE TRAVELED WAY OF THE ROAD SOUTH
- 6) 2.0' NORTH TO THE CENTERLINE TRAVELED WAY OF THE ROAD EAST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,648.46' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 30-19-13
- 2) 2,648.46' NORTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "BROSEMER LS 82" CAP HE SET FOR THE NORTHWEST CORNER OF SECTION 30-19-13
- 3) 2,644.22' EAST TO THE 1/2" REBAR WITH HIS "BROSEMER LS 82" CAP HE SET FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 30-19-13
- 4) 3,425.97' EAST TO THE 1/2" REBAR WITH HIS "BROSEMER LS 82" CAP HE SET FOR THE SOUTHEAST TRACT CORNER
- 5) 5,287.59' EAST TO THE 1/2" REBAR WITH HIS "BROSEMER LS 82" CAP HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 30-19-13

WEST QUARTER CORNER 30-19-13