

**NORTH 1/16<sup>TH</sup> CORNER SOUTHEAST QUARTER OF SECTION 31, TOWNSHIP 19 SOUTH, RANGE 13 EAST**

- 1) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 664 RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 84 FOR THE RECORD OF THE SURVEY OF A PUBLIC ROAD ALLOWED BY THE COUNTY COMMISSIONERS AND RECORDED IN VOLUME "E" ON PAGE 21 OF THE ROAD RECORDS AND SURVEYED ON THE 11<sup>TH</sup> AND 26<sup>TH</sup> DAYS OF JULY, 1911, SAID ROAD BEING LOCATED IN SECTION 31, TOWNSHIP 19, AND RANGE 13 EAST. THIS ROAD WAS ENTERED ON THE 28<sup>TH</sup> DAY OF JULY, 1911. HE NOTED THAT ALL OF THE MEASUREMENTS ON THE TOWNSHIP LINE AND THE EAST LINE OF THE SOUTHEAST 1/4 OF SECTION 31-19-13 SHOWED AN EXCESS OF SIX FEET TO THE MILE AND THEIR ALL CHECKING OUT WITH THE SAME EXCESS SHOWED THAT THE CHAINS USED BY THE GOVERNMENT SURVEYOR AT THE TIME OF THE FIRST SURVEY OF THIS LAND WAS LONGER THAN A STANDARD CHAIN AND GAVE AN EXCESS OF SIX FEET TO THE MILE, AND THIS EXCESS WAS TAKEN INTO CONSIDERATION IN THE ESTABLISHMENT OF THE ROAD STONES ON THIS ROAD SURVEY. **HE PLANTED A 12 X 7 X 3 INCH ROAD STONE MARKED "R" ON THE WEST SIDE** ON A LINE PARALLEL TO THE SOUTH LINE OF SECTION 31-19-13 AT 1,301-1/2 FEET WEST OF THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 31-19-13. HE NOTED THAT THIS ROAD WAS 40 FEET WIDE, 20 FEET EACH SIDE OF THE LINE AS DESCRIBED AND MARKED. HE DID **NOT** CALL THIS ROAD STONE THE 1/16<sup>TH</sup> CORNER, BUT IT IS LISTED HERE TO SHOW THE ORIGIN OF THIS ROAD STONE.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS 1,301-1/2 FEET EAST PARALLEL TO THE SOUTH LINE OF SECTION 31-19-13 TO THE CORNER STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 31-19-13 FOR THE BEGINNING OF THIS ROAD SURVEY. **HE SET A 12 X 6 X 3 INCH STONE ABOVE THE OLD STONE** TO MARK THE SIGHT OF THIS 1/4 CORNER.
- 2) THIS ROAD EXTENDS NORTH PARALLEL TO THE EAST LINE OF SECTION 31-19-13 FOR 1,380 FEET TO THE 18 X 8 X 12 INCH ROAD STONE MARKED "R" ON THE NORTH FACE FOR THE TERMINUS OF THIS ROAD SURVEY
- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 664 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 21 PETITIONED BY JOHN A. SHINKLE AND OTHERS FOR A ROAD IN TOWNSHIP 19-13 [PACKET 777 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] DATED JULY 1911, SAID THAT **HE PLANTED A 12 X 7 X 3 INCH ROAD STONE MARKED "R" ON THE WEST SIDE** ON A LINE PARALLEL TO THE SOUTH LINE OF SECTION 31-19-13 AT 1,301-1/2 FEET WEST OF THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 31-19-13. HE DID **NOT** CALL THIS ROAD STONE THE 1/16<sup>TH</sup> CORNER, BUT IT IS LISTED HERE TO SHOW THE ORIGIN OF THIS ROAD STONE. HE SAID TO SEE SURVEYOR RECORD 1 ON PAGE 84 FOR DESCRIPTIONS OF THE MARKS AND A LARGE PLAT.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS 1,301-1/2 FEET EAST PARALLEL TO THE SOUTH LINE OF SECTION 31-19-13 TO THE CORNER STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 31-19-13 FOR THE BEGINNING OF THIS ROAD SURVEY. **HE SET A 12 X 6 X 3 INCH STONE ABOVE THE OLD STONE** TO MARK THE SIGHT OF THIS 1/4 CORNER.
- 2) THIS ROAD EXTENDS NORTH PARALLEL TO THE EAST LINE OF SECTION 31-19-13 FOR 1,380 FEET TO THE 18 X 8 X 12 INCH ROAD STONE MARKED "R" ON THE NORTH FACE FOR THE TERMINUS OF THIS ROAD SURVEY

HIS INFORMATION IS CONTINUED ON PAGE 2

3) THIS ROAD IS FORTY FEET WIDE, TWENTY FEET ON EACH SIDE OF THE LINE AS DESCRIBED AND SURVEYED

3) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 4

ON MAY 1, 1911 A PETITION SIGNED BY JOHN A. SHINKLE AND OTHERS FOR THE LOCATION OF A ROAD IN TOWNSHIP 19-13 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON JUNE 23, 1911, AND THE FINAL ORDER FOR THE LOCATION OF THE FOLLOWING ROAD WAS ISSUED ON JULY 7, 1911.

1) BEGINNING 24 FEET EAST OF THE NORTHWEST CORNER OF THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 31-19-13; THENCE SOUTH 80 RODS TO A POINT 20 FEET EAST OF THE SOUTHWEST CORNER OF SAID SOUTHEAST 1/4 OF THE NORTHEAST 1/4; THENCE EAST ALONG THE SOUTH LINE OF SAID SOUTHEAST 1/4 OF THE NORTHEAST 1/4 TO THE SECTION LINE ROAD

2) ROAD TO BE 40 FEET WIDE, 20 FEET ON EACH SIDE OF THE LINE AS DESCRIBED

NORTH SIXTEENTH CORNER SOUTHEAST QUARTER 31-19-13