

**NORTH 1/16<sup>TH</sup> CORNER SOUTHWEST QUARTER OF SECTION 31, TOWNSHIP 19 SOUTH, RANGE 13 EAST**

1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED MARCH 19, 2002, FOR PROJECT NUMBER 02045-02, SURVEY F31002 IN THE SURVEY FILE FOR TOWNSHIP 19-13 FOR THE SURVEY OF A TRACT OF 194.5 ACRES LOCATED IN THE FRACTIONAL SOUTHWEST QUARTER AND THE FRACTIONAL SOUTHWEST QUARTER OF THE NORTHWEST QUARTER OF SECTION 31-19-13, SAID THAT **HE SET A 1/2" REBAR WITH HIS "LS 752" CAP** FOR THE NORTH 1/16<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 31-19-13 AT 20.00 CHAINS WEST OF THE CENTER CORNER OF SECTION 31-19-13 AS PER THE GLO.

- 1) THE CORNER FALLS IN CULTIVATION
- 2) A STEEL FENCE POST IS NEXT TO THE REBAR
- 3) 453.75' NORTH TO A 1/2" REBAR WITH HIS "LS 752" CAP SET
- 4) 786.85' EAST TO A 1/2" REBAR WITH HIS "LS 752" CAP SET
- 5) 1,326.22' WEST TO A 1/2" REBAR WITH HIS "LS 752" CAP SET

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,320.00' EAST TO THE CORPS OF ENGINEERS MONUMENT BRASS CAP IN CONCRETE HE FOUND AT THE NORTHEAST CORNER OF THE FRACTIONAL SW1/4 OF SECTION 31-19-13
- 2) 1,326.22' WEST TO THE 1" PIN FOUND AT THE NORTHWEST CORNER OF THE FRACTIONAL SW1/4 OF SECTION 32-19-13 ON THE RANGE LINE
- 3) 1,321.77' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE FRACTIONAL SW1/4 OF THE NW1/4 OF SECTION 31-19-13
- 4) 2,643.54' NORTH TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE FRACTIONAL NW1/4 OF THE NW1/4 OF SECTION 31-19-13

2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F31003 IN THE SURVEY FILE FOR TOWNSHIP 19-13 FOR THE SURVEY OF AN 18.38 ACRE TRACT IN THE FRACTIONAL NORTHWEST QUARTER AND THE NORTHEAST QUARTER OF SECTION 31-19-13 FOR PROJECT NUMBER 03145-02 DATED APRIL 28, 2003, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A 1/2" REBAR WITH A "LS 82" CAP** AT THE NORTH 1/16<sup>TH</sup> CORNER OF THE SOUTHWEST 1/4 OF SECTION 31-19-13.

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,320.00' EAST TO THE CORPS OF ENGINEERS MONUMENT [BRASS CAP IN CONCRETE] FOUND AT THE CENTER CORNER OF SECTION 31-19-13
- 2) 2,027' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE 18.38 ACRE TRACT
- 3) 3,959.46' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 31-19-13
- 4) 1,326.22' WEST TO THE 1" PIN HE FOUND AT THE NORTHWEST CORNER OF THE FRACTIONAL SW1/4 OF SECTION 32-19-13
- 5) 1,321.77' NORTH TO THE 1/2" REBAR WITH "LS 82" CAP HE FOUND AT THE CENTER CORNER OF THE NW1/4 OF SECTION 31-19-13
- 6) 2,643.54' NORTH TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE FRACTIONAL NW1/4 OF THE NW1/4 OF SECTION 31-19-13

NORTH SIXTEENTH CORNER SOUTHWEST QUARTER 31-19-13