

WEST 1/4 CORNER SECTION 31, TOWNSHIP 19 SOUTH, RANGE 13 EAST

- 1) ON PAGE 87 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 3-1/2"** FOR THE WEST 1/4 CORNER OF SECTION 31-19-13 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 24, 1855.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 22" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-19-13
 - 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 24" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO TOWNSHIPS 19 & 20 SOUTH, RANGES 12 & 13 EAST AT THE SOUTHWEST CORNER OF SECTION 31-19-13
- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 28 RECORDED IN SURVEY BOOK "A" ON PAGES 122 & 123 DATED MARCH 18-20, 1868 TO SURVEY J. OGDEN'S AND C. ARCHER'S LAND, BEING THE WEST 1/2 OF THE NORTHEAST 1/4, AND THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4, AND THE NORTH 1/2 OF THE SOUTHEAST 1/4 OF SECTION 36-19-12, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 36-19-12 ON THE RANGE LINE ON THIS SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 161 RODS, 5 LINKS NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-19-12
 - 2) 80 RODS, 5 LINKS SOUTH ON THE RANGE LINE TO THE STONE HE SET FOR THE 1/2/4 CORNER ON THE EAST SIDE OF THE SE1/4 OF SECTION 36-19-12
 - 3) 160 RODS, 10 LINKS SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 36-19-12 ON THE TOWNSHIP LINE
- 3) JOHN R. YOUNG, L.S. 112, FOR THE PARTIAL BOUNDARY SURVEYS FOR THE JOHN REDMOND DAM AND RESERVOIR, CONTRACT NUMBER DACW56-75-C-0129 IN JUNE 1975, SURVEY F31001 IN THE SURVEY FILE FOR TOWNSHIP 19-13, SAID THAT **HE SET A 1" X 2' IRON BAR** FOR THE WEST 1/4 CORNER OF SECTION 31-19-13 ON THE RANGE LINE AT HALFWAY BETWEEN THE "ORIGINAL STONE" THAT HE FOUND AT THE NORTHWEST CORNER AND THE "ORIGINAL STONE" THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-19-13 ON THE TOWNSHIP LINE.
- 1) 36.37' N. 77° 30' E. TO A SPIKE & WASHER IN THE TOP OF A FENCE POST
 - 2) 40.13' N. 72° 50' W. TO A SPIKE & 3 WASHERS IN A BLAZED 50" WALNUT TREE
 - 3) 24.167' S. 62° 00' W. TO A SPIKE & 2 WASHERS IN A BLAZED 20" LOCUST TREE
 - 4) 275' SOUTH TO THE ABUTMENT OF A WASHED OUT BRIDGE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,647.26' NORTH ON THE RANGE LINE TO THE "ORIGINAL STONE" HE FOUND AT THE NORTHWEST CORNER OF SECTION 31-19-13
 - 2) 2,647.26' SOUTH ON THE RANGE LINE TO THE "ORIGINAL STONE" HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-19-13 ON THE TOWNSHIP LINE
 - 3) 2,330.74' EAST TO THE STANDARD CORPS OF ENGINEERS MONUMENT HE SET FOR A TRACT CORNER
 - 4) 2,645.74' EAST TO THE STANDARD CORPS OF ENGINEERS MONUMENT HE SET FOR THE CENTER CORNER OF SECTION 31-19-13
 - 5) 5,285.20' EAST TO THE "ORIGINAL STONE" HE FOUND AT THE EAST 1/4 CORNER OF SECTION 31-19-13
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 19, 2002, FOR PROJECT NUMBER 02045-02, SURVEY F31002 IN THE SURVEY FILE FOR TOWNSHIP 19-13 FOR THE SURVEY OF A TRACT OF 194.5 ACRES LOCATED IN THE FRACTIONAL SOUTHWEST QUARTER AND THE FRACTIONAL SOUTHWEST QUARTER OF THE NORTHWEST QUARTER OF

SECTION 31-19-13, SAID THAT **HE FOUND THE 1" IRON BAR** AT THE WEST 1/4 CORNER OF SECTION 31-19-13 ON THE RANGE LINE FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE.

- 1) 35.95' SW TO A 40 D NAIL & BOTTLE CAP IN A 10" KENTUCKY COFFEE TREE
- 2) 38.5' NW TO A 40 D NAIL & BOTTLE CAP IN A 9" HEDGE TREE
- 3) 25.0' EAST TO A 1/2" X 24" REBAR SET
- 4) 2.5' WEST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,647.10' SOUTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE FRACTIONAL SW1/4 OF SECTION 31-19-13 ON THE TOWNSHIP LINE
- 2) 1,323.62' NORTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE FRACTIONAL SW1/4 OF THE NW1/4 OF SECTION 31-19-13
- 3) 2,647.42' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE FRACTIONAL NW1/4 OF THE NW1/4 OF SECTION 31-19-13
- 4) 1,326.22' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE FRACTIONAL SW1/4 OF THE NW1/4 OF SECTION 31-19-13
- 5) 2,646.22' EAST TO THE CORPS OF ENGINEERS MONUMENT BRASS CAP IN CONCRETE HE FOUND AT THE NORTHEAST CORNER OF THE FRACTIONAL SW1/4 OF SECTION 31-19-13

- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 28, 2003, FOR PROJECT NUMBER 03145-02, SURVEY F31003 IN THE SURVEY FILE FOR TOWNSHIP 19-13 FOR THE SURVEY OF AN 18.38 ACRE TRACT IN THE FRACTIONAL NORTHWEST QUARTER AND THE NORTHEAST QUARTER OF SECTION 31-19-13, SAID THAT **HE FOUND THE 1" IRON PIN** AT THE WEST 1/4 CORNER OF SECTION 31-19-13 ON THE RANGE LINE FROM HIS EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE DATED MARCH 2002.

- 1) 35.95' SW TO A 40 D NAIL & BOTTLE CAP IN A 10" KENTUCKY COFFEE TREE
- 2) 38.5' NW TO A 40 D NAIL & BOTTLE CAP IN A 9" HEDGE TREE
- 3) 25.0' EAST TO A 1/2" X 24" REBAR SET
- 4) 2.5' WEST TO THE CENTERLINE TRAVELED WAY OF THE ROAD NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323.62' NORTH ON THE RANGE LINE TO THE 1/2" REBAR WITH A "LS 82" CAP HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 31-19-13
- 2) 1,796.62' NORTH ON THE RANGE LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE 18.38 ACRE TRACT
- 3) 2,647.42' NORTH ON THE RANGE LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE FRACTIONAL NW1/4 OF THE NW1/4 OF SECTION 31-19-13
- 4) 1,326.22' EAST TO THE 1/2" REBAR WITH A "LS 82" CAP HE FOUND AT THE SOUTH 1/16TH CORNER OF THE SE1/4 OF SECTION 31-19-13
- 5) 2,646.22' EAST TO THE CORPS OF ENGINEERS MONUMENT BRASS CAP IN CONCRETE HE FOUND AT THE CENTER CORNER OF SECTION 31-19-13
- 6) 3,352.22' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE 18.38 ACRE TRACT
- 7) 5,285.68' EAST TO THE 5/8" REBAR WITH LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 31-19-13

WEST QUARTER CORNER 31-19-13