

CENTER CORNER OF SECTION 32, TOWNSHIP 19 SOUTH, RANGE 13 EAST

- 1) W. D. KRETSINGER, L.S. 363, COUNTY ENGINEER, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 2 AT THE REQUEST OF GEORGE ROSENQUIST TO LOCATE AND PERMANENTLY ESTABLISH THE HALF SECTION LINE BETWEEN THE NORTH 1/2 AND THE SOUTH 1/2 OF SECTION 32-19-13, SAID THAT PRIOR TO THE DATE OF THE SURVEY CONSIDERABLE TIME WAS SPENT LOCATING SUCH STONES AS COULD BE FOUND THAT WOULD GIVE US A CHECK ON THE LOCATION OF THE STONES FOUND IN PLACE AT THE EAST AND WEST 1/4 CORNERS OF SECTION 32-19-13. **HE SET AN IRON PIN NEAR THE CENTER CORNER OF SECTION 32-19-13** ON LINE BETWEEN THE STONE THAT HE FOUND IN PLACE AT THE WEST 1/4 CORNER OF SECTION 32-19-13 AND THE STONE THAT HE FOUND IN PLACE AT THE EAST 1/4 CORNER OF SECTION 32-19-13, AND ON A LINE **ASSUMED** BY ALL PRESENT TO BE ON THE NORTH & SOUTH 1/2 SECTION LINE ON THIS **PERMANENT SURVEY**. THE SURVEY BEGAN MAY 3, 1954 AND WAS COMPLETED ON MAY 7, 1954.

- 2) JOHN R. YOUNG, L.S. 112, OF SCHWAB-EATON, P.A., IN A SECTION CORNER REPORT FOR THE PARTIAL BOUNDARY SURVEYS FOR THE JOHN REDMOND DAM AND RESERVOIR UNDER CONTRACT NUMBER DACW56-75-C-0129 DATED JUNE 1975, SURVEY F32004 IN THE SURVEY FILE FOR TOWNSHIP 19-13, SAID THAT **HE SET A 1" X 2' IRON BAR** FOR THE CENTER CORNER OF SECTION 32-19-13 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE QUARTER CORNERS.
 - 1) N. 41°30' W. 6.64' TO A SPIKE & WASHER IN A BLAZED 10" LOCUST TREE
 - 2) N. 79°00' E. 10.57' TO A SPIKE & 2 WASHERS IN A BLAZED 15" ELM TREE
 - 3) S. 77°20' W. 8.69" TO A SPIKE & 3 WASHERS IN A BLAZED 20" LOCUST TREE
 - 4) 100' WEST OF THE EAST EDGE OF THE TIMBER

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,632.99' WEST TO THE ORIGINAL STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 32-19-13
 - 2) 2,612.21' NORTH TO THE 1" BAR HE SET FOR THE NORTH 1/4 CORNER OF SECTION 32-19-13 **[NOTE: HE DID NOT FIND THE STONE THAT IS AT THE NORTH 1/4 CORNER OF SECTION 32-19-13! WARREN CHIP WOODS, L.S 603, COUNTY SURVEYOR]**
 - 3) 2,636.15' EAST TO THE ORIGINAL STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 32-19-13
 - 4) 2,644.74' SOUTH TO THE 1" IRON BAR HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 32-19-13 ON THE TOWNSHIP LINE **[NOTE: HE DID NOT FIND THE BUGGY AXLE DRIVEN THROUGH THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 32-19-13 FROM THE 1954 PERMANENT SURVEY! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**

- 3) JOHN R. YOUNG, L.S. 112, IN SURVEY F32002 IN THE SURVEY FILES FOR TOWNSHIP 19-13 FOR A *CERTIFICATE OF SURVEY* FOR A 15.24 ACRE TRACT OF LAND IN THE NORTH HALF OF SECTION 32-19-13 DATED MAY 1983, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND A BAR** AT THE CENTER CORNER OF SECTION 32-19-13. THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,632.99' WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 32-19-13
 - 2) 2,609.67' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 32-19-13
 - 3) 2,634.15' EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 32-19-13

CENTER CORNER 32-19-13