

**NORTH 1/16<sup>TH</sup> CORNER SOUTHEAST QUARTER OF SECTION 32, TOWNSHIP 19 SOUTH,  
RANGE 13 EAST**

- 1) W. D. KRETSINGER, L.S. 363, COUNTY ENGINEER, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 2 AT THE REQUEST OF GEORGE ROSENQUIST TO LOCATE AND PERMANENTLY ESTABLISH THE HALF SECTION LINE BETWEEN THE NORTH 1/2 AND THE SOUTH 1/2 OF SECTION 32-19-13, SAID THAT PRIOR TO THE DATE OF THE SURVEY CONSIDERABLE TIME WAS SPENT LOCATING SUCH STONES AS COULD BE FOUND THAT WOULD GIVE US A CHECK ON THE LOCATION OF THE STONES FOUND IN PLACE AT THE EAST AND WEST 1/4 CORNERS OF SECTION 32-19-13. **HE SET AN IRON PIN AT THE APPROXIMATE** NORTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 32-19-13 ON LINE BETWEEN THE STONE THAT HE FOUND IN PLACE AT THE WEST 1/4 CORNER OF SECTION 32-19-13 AND THE STONE THAT HE FOUND IN PLACE AT THE EAST 1/4 CORNER OF SECTION 32-19-13 ON THIS **PERMANENT SURVEY**.

NORTH SIXTEENTH CORNER SOUTHEAST QUARTER 32-19-13