

**WEST 1/16TH CORNER SOUTHWEST QUARTER OF SECTION 33, TOWNSHIP 19 SOUTH,
RANGE 13 EAST**

- 1) E. B. KIRKENDALL, COUNTY SURVEYOR FROM 1863 TO 1865, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "A" ON PAGE 40 [PACKET 160 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY S. VANGUNDY AND OTHER FOR THE "NEOSHO RAPIDS TO HARTFORD ROAD" THAT WAS SURVEYED JULY 15 & 16, 1863, AND ESTABLISHED IN THE COMMISSIONERS JOURNAL ON PAGE 49, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF THE SOUTH 1/2 OF THE SOUTHWEST 1/4 OF SECTION 33-19-13 THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO THE SOUTHEAST CORNER OF NEOSHO RAPIDS AT THE SOUTHEAST CORNER OF SEC. 29-19-11
2) THIS ROAD EXTENDS EAST ON THE 1/4 SECTION LINE TO THE CENTERLINE OF SECTION 33-19-13 AT A TURN TO THE SOUTH

- 2) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 129 RECORDED IN SURVEY BOOK "A" ON PAGES 213 & 214 DATED JUNE 30, 1869 TO ESTABLISH THE 1/4 CORNER ON THE WESTERN BOUNDARY AND ALSO A CORER EQUIDISTANT BETWEEN IT AND THE SOUTHWEST CORNER, AND ALSO BETWEEN IT AND THE NORTHWEST SECTION CORNER, AND ALSO CORRESPONDING CORNERS ON THE EASTERN BOUNDARY, AND ALSO RUN A LINE FROM THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 TO CORRESPONDING CORNER ON THE WESTERN BOUNDARY AND ESTABLISH A CORNER 80 RODS, ALSO 88 RODS, AND 160 RODS, MORE OR LESS, ACCORDING TO THE SIZE OF THE SECTION, AND ALSO ESTABLISH THE NORTHWEST CORNER OF THE SOUTHEAST 1/4 OF THE NORTHEAST 1/4 OF SECTION 33-19-13, SAID THAT **HE SET A STONE** FOR THE WEST 1/2/4 CORNER OF THE SOUTHWEST 1/4 OF SECTION 33-19-13 EQUIDISTANT BETWEEN THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-19-13 ON THE TOWNSHIP LINE AND THE STONE THAT HE SET FOR THE WEST 1/4 CORNER OF SECTION 33-19-13 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 80 RODS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-19-13 ON THE TOWNSHIP LINE
2) 80 RODS NORTH TO THE STONE HE SET FOR THE WEST 1/4 CORNER OF SECTION 33-19-13
3) 160 RODS NORTH TO THE STONE HE SET FOR THE WEST 1/2/4 CORNER OF THE NW1/4 OF SECTION 33-19-13
4) 240 RODS NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-19-13
5) 316 RODS, 24 LINKS EAST TO THE STONE HE SET FOR THE EAST 1/2/4 CORNER OF THE SE1/4 OF SECTION 33-19-13

- 3) LLOYD J. DOBLER, L.S. 541, FOR THE "PARTIAL BOUNDARY SURVEYS "AREA A" JOHN REDMOND RESERVOIR" WITH NO READABLE DATE BUT AROUND 1975 AND SURVEY F33001 IN SURVEY DRAWER FOR TOWNSHIP 19-13, SAID THAT **HE SET A STANDARD CORPS OF ENGINEERS WITNESS MONUMENT 10 FEET EAST OF THE TRUE POSITION** OF THE WEST 1/16TH CORNER OF THE SOUTHWEST 1/4 OF SECTION 33-19-13. HE DID NOT DESCRIBE THE METHODOLOGY HE USED TO DETERMINE THE LOCATION OF THE CORNER. **[NOTE: VERIFY BEFORE USING AS HE DID NOT FIND THE STONE AT THE WEST 1/4 CORNER OF SECTION 33-19-13!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**

HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES FROM THE TRUE POSITION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 1,319.30' SOUTH TO THE IRON PIN HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-19-13 ON THE TOWNSHIP LINE
- 2) 1,319.30' NORTH TO THE STANDARD CORPS OF ENGINEERS MONUMENT HE SET FOR THE WEST 1/4 CORNER OF SECTION 33-19-13 **[NOTE: HE DID NOT FIND THE STONE AT THE WEST 1/4 CORNER OF SECTION 33-19-13 – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**
- 3) 1,759.30' NORTH TO THE STANDARD CORPS OF ENGINEERS MONUMENT HE SET AT 10' EAST ON COURSE 3
- 4) 3,968.24' NORTH TO THE IRON PIN HE FOUND AT THE NORTHWEST CORNER OF SECTION 33-19-13

WEST SIXTEENTH CORNER SOUTHWEST QUARTER 33-19-13