

**CENTER CORNER OF SECTION 34, TOWNSHIP 19 SOUTH, RANGE 13 EAST**

- 1) W. D. KRETSINGER, L.S. 363, COUNTY ENGINEER, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 1 DATED MARCH 04, 1954 AT THE REQUEST OF WILL REEBLE TO LOCATE AND PERMANENTLY ESTABLISH THE LINE BETWEEN THE EAST 1/2 AND THE WEST 1/2 OF SECTION 34-19-13 THAT WAS ADJOURNED FROM FEBRUARY 25 TO MARCH 4, 1954, SAID THAT **HE SET AN IRON PIN IN LINE WITH A HEDGE TO THE WEST** FOR THE CENTER CORNER OF SECTION 34-19-13 ON THIS **PERMANENT SURVEY**. HE NOTED THAT THE HEDGE TO THE SOUTH WAS FOUND TO BE 4' TO 5' EAST OF THE LINE BETWEEN THE CENTER CORNER AND THE SOUTH 1/4 CORNER OF SECTION 34-19-13 ON THE TOWNSHIP LINE.
  
- 2) LLOYD J. DOBLER, L.S. 541, OF PROFESSIONAL ENGINEERING CONSULTANTS, FOR CONTRACT DACW56-70-C-0158, FOR THE "PARTIAL BOUNDARY SURVEYS "AREA A" JOHN REDMOND RESERVOIR", SURVEY F34001 IN THE SURVEY FILE FOR TOWNSHIP 19-13, WITH NO READABLE DATE BUT AROUND 1975, SHOWS ON HIS SURVEY DRAWING THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE CENTER CORNER OF SECTION 34-19-13 TO BE AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS, BUT THIS POSITION WAS **NOT** MONUMENTED ON THIS SURVEY,  
**HIS DRAWING SHOWS THE FOLLOWING INFORMATION:**
  - 1) 2,643.76' WEST TO THE IRON PIN HE SET FOR THE WEST 1/4 CORNER OF SECTION 34-19-13
  - 2) 2,643.66' NORTH TO THE IRON PIN HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 34-19-13
  - 3) 2,643.61' EAST TO THE IRON PIN HE SET FOR THE EAST 1/4 CORNER OF SECTION 34-19-13
  - 4) 2,643.68' SOUTH TO THE IRON PIN HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 34-19-13 ON THE TOWNSHIP LINE

CENTER CORNER 34-19-13