

NORTH 1/4 CORNER SECTION 34, TOWNSHIP 19 SOUTH, RANGE 13 EAST

- 1) ON PAGE 652 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 34-19-13.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.02 CHAINS WEST TO THE 20" X 14" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-19-13
 - 2) 40.02 CHAINS EAST TO THE 20" X 15" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-19-13 ON THE COUNTY LINE
- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGES 15 & 16 FOR LYMAN FRY, W. R. & C. H. COLE, JAMES A. ALLER, WILLIAM A. JONES, OTTO J. JOHNSON, E. T. WHITE, JESSIE FLEMING, C. B. HILL, JAMES C. GAMBLE, AND HENRY JACOB REQUESTING A SURVEY TO PERMANENTLY ESTABLISH THE CORNERS AND BOUNDARIES OF THE FOLLOWING DESCRIBED LANDS: NORTHEAST 1/4 OF SECTION 27; SOUTHEAST 1/4, NORTHEAST 1/4, & WEST 1/2 OF NORTHEAST 1/4 OF SECTION 22; WEST 1/2 & SOUTHEAST 1/4 OF THE NORTHEAST 1/4 AND THE NORTHEAST 1/4 OF THE NORTHEAST 1/4, EAST 1/2 OF NORTHWEST 1/4 & NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 15; THE EAST 1/2 AND SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 AND THE SOUTH 1/2 OF THE NORTHEAST 1/4 LYING SOUTH OF THE INDIAN RESERVATION IN SECTION 10; THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 3, ALL IN TOWNSHIP 19, RANGE 13, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 27-19-13 ON THIS **PERMANENT SURVEY**. THE SURVEY BEGAN APRIL 30 AND WAS COMPLETED AUGUST 9, 1894, AND WAS FILED ON AUGUST 27, 1984.

HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 39.98 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-19-13
 - 3) 39.98 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 27-19-13 ON THE LYON AND COFFEY COUNTY LINE
- 3) W. D. KRETSINGER, L.S. 363, COUNTY ENGINEER, BY LESLIE M. GOULD, L.S. 142, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 2 ON PAGE 1 DATED MARCH 04, 1954 AT THE REQUEST OF WILL REEBLE TO LOCATE AND PERMANENTLY ESTABLISH THE LINE BETWEEN THE EAST 1/2 AND THE WEST 1/2 OF SECTION 34-19-13 THAT WAS ADJOURNED FROM FEBRUARY 25 TO MARCH 4, 1954, SAID THAT **HE SET AN IRON PIN** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 34-19-13 ON THIS **PERMANENT SURVEY**. HE SET THIS CORNER ON LINE AND AT THE PRORATION BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 34-19-13 AND THE 1/8TH CORNER STONE THAT HE FOUND AT THE NORTHEAST CORNER OF THE NORTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 34-19-13, THAT WAS FOUND IN THE COURSE OF A LEGAL SURVEY BY MATTHEW BROWN IN 1894 IN PERMANENT SURVEY BOOK 1 ON PAGE 16. THERE ARE NO TIES ON THIS PERMANENT SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,640.5' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 34-19-13
- 2) 1,320.5' EAST TO THE 1/8TH CORNER STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF THE NE1/4 OF SECTION 34-19-13, THAT WAS FOUND IN THE COURSE OF A LEGAL SURVEY BY MATTHEW BROWN IN 1894 IN PERMANENT SURVEY BOOK 1 ON PAGE 16 AND WAS 1,320' WEST OF THE NORTHEAST CORNER OF SECTION 34-19-13

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 2,640.5' EAST TO THE IRON PIN HE SET FOR THE PERMANENT NORTHEAST CORNER OF SECTION 34-19-13 ON THE LYON AND COFFEY COUNTY LINE

- 4) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 106 SHOWS AN **IRON PIN** AT THE "N1/4 CORNER SECTION 34-19-13" ON FEBRUARY 12, 1954.
 - 1) 19.9' SE TO A SPIKE IN THE WEST SIDE OF AN ELM TREE
 - 2) 42.9' NE TO A SPIKE IN A TELEPHONE POLE
 - 3) 28.5' SW TO A BENT SPIKE IN A LOCUST TREE

- 5) THE KRETSINGER REFERENCE TIE BOOKS FOR TOWNSHIP 19-13 SHOWS AN **IRON PIN** AT THE "N1/4 CORNER SECTION 34-19-13".
 - 1) 19.9' SE TO A SPIKE & WASHER IN THE WEST SIDE OF AN ELM TREE
 - 2) 42.9' NE TO A SPIKE & WASHER IN A TELEPHONE POLE
 - 3) 28.5' SW TO A BENT SPIKE IN A LOCUST TREE

- 6) LLOYD J. DOBLER, L.S. 541, OF PROFESSIONAL ENGINEERING CONSULTANTS, FOR CONTRACT DACW56-70-C-0158, FOR THE "PARTIAL BOUNDARY SURVEYS "AREA A" JOHN REDMOND RESERVOIR", SURVEY F34001 IN THE SURVEY FILE FOR TOWNSHIP 19-13, WITH NO READABLE DATE BUT AROUND 1975, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND AN IRON PIN** AT THE NORTH 1/4 CORNER OF SECTION 34-19-13. [**NOTE:** HE DID NOT DESCRIBE THE METHODOLOGY HE USED TO DETERMINE THAT THIS IRON PIN WAS THE NORTH 1/4 CORNER OF SECTION 34-19-13 AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,639.62' WEST TO THE IRON PIN HE FOUND AT THE NORTHWEST CORNER OF SECTION 34-19-13
 - 2) 2,639.26' EAST TO THE IRON PIN HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-19-13 ON THE LYON AND COFFEE COUNTY LINE
 - 3) 2,643.66' SOUTH TO THE THEORETICAL LOCATION FOR THE CENTER CORNER OF SECTION 34-19-13
 - 4) 5,287.34' SOUTH TO AN IRON PIN HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 34-19-13 ON THE TOWNSHIP LINE

NORTH QUARTER CORNER 34-19-13