

WEST 1/4 CORNER SECTION 34, TOWNSHIP 19 SOUTH, RANGE 13 EAST

- 1) ON PAGE 651 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 33 & 34-19-13.
- 2) H. S. SLEEPER, BRECKENRIDGE COUNTY SURVEYOR FROM 1859 TO 1862, IN SURVEY NUMBER 20 RECORDED IN SURVEY BOOK "A" ON PAGE 58 DATED AUGUST 1860, TO SUBDIVIDE SECTION 33-19-13 AND ESTABLISH THE MIDDLE CORNER AND ALSO THE 80 CORNER ON THE EAST LINE OF THE SOUTHWEST 1/4 OF SECTION 33, INDICATES ON HIS SURVEY DRAWING THAT **HE FOUND** THE EAST 1/4 CORNER OF SECTION 33-19-13. HE DOES NOT DESCRIBE THE MONUMENT THAT HE FOUND ON THIS SURVEY.
- 3) D. T. McAULEY, COUNTY SURVEYOR FROM 1867 TO 1870, IN SURVEY NUMBER 129 RECORDED IN SURVEY BOOK "A" ON PAGES 213 & 214 DATED JUNE 30, 1869 TO ESTABLISH THE 1/4 CORNER ON THE WESTERN BOUNDARY AND ALSO A CORNER EQUIDISTANT BETWEEN IT AND THE SOUTHWEST CORNER, AND ALSO BETWEEN IT AND THE NORTHWEST SECTION CORNER, AND ALSO CORRESPONDING CORNERS ON THE EASTERN BOUNDARY, AND ALSO RUN A LINE FROM THE NORTHEAST CORNER OF THE SOUTHWEST 1/4 OF THE SOUTHWEST 1/4 TO CORRESPONDING CORNER ON THE WESTERN BOUNDARY AND ESTABLISH A CORNER 80 RODS, ALSO 88 RODS, AND 160 RODS, MORE OR LESS, ACCORDING TO THE SIZE OF THE SECTION, AND ALSO ESTABLISH THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF THE NORTHEAST 1/4 OF SECTION 33-19-13, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 33-19-13 ON THIS SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 79 RODS, 10 LINKS NORTH TO THE STONE HE SET FOR THE NORTHEAST CORNER OF THE SE1/4 OF THE NE1/4 OF SECTION 33-17-13
 - 2) 158 RODS, 20 LINKS NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 33-17-13
 - 3) 79 RODS, 8-1/2 LINKS SOUTH TO THE STONE HE SET FOR THE EAST 1/2/4 CORNER OF THE SE1/4 OF SECTION 33-17-13
 - 4) 158 RODS, 17 LINKS SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-17-13 ON THE TOWNSHIP LINE
- 4) LLOYD J. DOBLER, L.S. 541, OF PROFESSIONAL ENGINEERING CONSULTANTS, FOR CONTRACT DACW56-70-C-0158, FOR THE "PARTIAL BOUNDARY SURVEYS "AREA A" JOHN REDMOND RESERVOIR", SURVEY F33001 IN THE SURVEY FILE FOR TOWNSHIP 19-13, WITH NO READABLE DATE BUT AROUND 1975, SHOWS ON HIS SURVEY DRAWING THAT **HE SET AN IRON PIN** FOR THE EAST 1/4 CORNER OF SECTION 33-17-13 ON LINE AND HALFWAY BETWEEN THE NORTHEAST AND SOUTHWEST CORNERS OF SECTION 33-17-13. HE DID NOT DESCRIBE THE IRON PIN OR TURN IN ANY TIES TO THE COUNTY ENGINEER'S OFFICE. **[NOTE: VERIFY BEFORE USING AND CHECK FOR THE STONE OF RECORD AS THE SURVEY FOR JOHN REDMOND WERE POORLY DONE AND SOME CORNERS WERE APPARENTLY "HEELED-IN" - WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 661.69' SOUTH TO THE STANDARD CORPS OF ENGINEERS MONUMENT HE SET FOR A TRACT CORNER
- 2) 2,646.77' SOUTH TO THE IRON PIN HE FOUND AT THE SOUTHWEST CORNER OF SECTION 33-17-13

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 2,646.77' NORTH TO THE IRON PIN HE FOUND AT THE NORTHEAST CORNER OF SECTION 33-17-13
 - 4) 2,636.97' WEST TO THE THEORETICAL LOCATION FOR THE CENTER CORNER OF SECTION 33-17-13
 - 5) 5,280.71' WEST TO THE STANDARD CORPS OF ENGINEERS MONUMENT HE SET FOR THE WEST 1/4 CORNER OF SECTION 33-19-13
- 5) LLOYD J. DOBLER, L.S. 541, OF PROFESSIONAL ENGINEERING CONSULTANTS, FOR CONTRACT DACW56-70-C-0158, FOR THE "PARTIAL BOUNDARY SURVEYS "AREA A" JOHN REDMOND RESERVOIR", SURVEY F34001 IN THE SURVEY FILE FOR TOWNSHIP 19-13, WITH NO READABLE DATE BUT AROUND 1975, SHOWS ON HIS SURVEY DRAWING THAT **HE SET AN IRON PIN** FOR THE WEST 1/4 CORNER OF SECTION 34-19-13 ON LINE AND HALFWAY BETWEEN THE NORTHWEST AND SOUTHWEST CORNERS OF SECTION 34-19-13. HE DID NOT DESCRIBE THE IRON PIN OR TURN IN ANY TIES TO THE COUNTY ENGINEER'S OFFICE. **[NOTE: VERIFY BEFORE USING AND CHECK FOR THE STONE OF RECORD AS THE SURVEY FOR JOHN REDMOND WERE POORLY DONE AND SOME CORNERS WERE APPARENTLY "HEELED-IN" - WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**
- HIS DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 661.69' SOUTH TO THE STANDARD CORPS OF ENGINEERS MONUMENT HE SET FOR A TRACT CORNER
 - 2) 2,646.77' SOUTH TO THE IRON PIN HE FOUND AT THE SOUTHWEST CORNER OF SECTION 34-19-13
 - 3) 2,646.77' NORTH TO THE IRON PIN HE FOUND AT THE NORTHWEST CORNER OF SECTION 34-19-13
 - 4) 2,643.76' EAST TO THE THEORETICAL LOCATION FOR THE CENTER CORNER OF SECTION 34-19-13
 - 5) 5,287.37' EAST TO THE IRON PIN HE SET FOR THE EAST 1/4 CORNER OF SECTION 34-19-13

WEST QUARTER CORNER 34-19-13