

WEST 1/4 CORNER SECTION 01, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 227 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 27" X 17" X 1-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 1 & 2-20-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 38.96 CHAINS NORTH TO THE 30" X 15" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1 & 2=20-10 ON THE TOWNSHIP LINE
 - 2) 40.00 CHAINS SOUTH TO THE 24" X 20" X 4-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1, 2, 11 & 12-20-10

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 130 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 52 DATED JANUARY 7, 1874 TO ESTABLISH THE CENTER CORNER AND THE 1/16TH CORNERS ON THE CENTER LINES AND SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 2-20-10 BY A LINE RUNNING NORTH AND SOUTH, SAID THAT **HE RESET THE ORIGINAL STONE THAT HE FOUND LYING ON THE GROUND** FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 2-20-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,320' NORTH TO THE 28" X 18" X 4" LIMESTONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE NE1/4 OF SECTION 2-20-10
 - 2) 2,580' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 2-20-10 ON THE TOWNSHIP LINE
 - 3) 2,635' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 2-20-10
 - 4) 1,322' WEST TO THE 14" X 14" X 2-1/2" LIMESTONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NE1/4 OF SECTION 2-20-10
 - 5) 2,644' WEST TO THE 18" X 6" X 2" LIMESTONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 2-20-10
 - 6) 3,959' WEST TO THE 18" X 12" X 5" LIMESTONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE NW1/4 OF SECTION 2-20-10
 - 7) 5,274 WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SEC. 2-20-10

- 3) FINNEY & TURNIPSEED PLANS FOR PROJECT 56-RS-27 (11) SHOW THAT **THEY SET A 5/8" REBAR AT THE "FENCE LINE"** FOR THE WEST 1/4 CORNER OF SECTION 1-20-10. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS TIS 5/8" REBAR MAY HAVE BEEN "HEELED-IN" FOR THIS BRIDGE SURVEY - WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 33.46' ENE TO A SPIKE IN THE TOP OF A FENCE POST
 - 2) 33.70' ESE TO A SPIKE IN THE TOP OF A FENCE POST
 - 3) 35.50' NW TO A SPIKE IN THE TOP OF A FENCE POST

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 29, 2012 FOR PROJECT NUMBER 12142-02, SURVEY F02002 IN THE SURVEY FILE FOR TOWNSHIP 20-10 FOR A SURVEY OF AN 8.62 ACRE TRACT IN THE NORTHEAST 1/4 OF SECTION 2-20-10 FOR THAD ROBERTS, SAID THAT **HE RECOVERED THE ORIGINAL 3/4" REBAR** AT THE EAST 1/4 CORNER OF SECTION 2-20-10 FROM REFERENCE TIES IN THE LYON COUNTY ENGINEER'S OFFICE. **HE REPLACED THIS REBAR WITH A 5/8" X 30" REBAR WITH A LYON COUNTY CAP** FOR THE EAST 1/4 CORNER OF SECTION 2-20-10.
 - 1) IN THE CENTERLINE OF TRAVELED WAY OF COUNTY ROAD "F" NORTH-SOUTH
 - 2) 65.13' EAST TO A LINE OF FENCE RUNNING NORTH AND SOUTH
 - 3) 60.00' WEST TO A LINE OF FENCE RUNNING NORTH AND SOUTH
 - 4) 2,637.45' SOUTH TO THE SOUTHEAST CORNER OF SECTION 2

HIS TIES ARE CONTINUED ON PAGE 2

- 5) 2,572.36' NORTH TO THE NORTHEAST CORNER OF SECTION 2
- 6) NO OTHER TIES AVAILABLE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION

- 1) 290.19' NORTH TO THE TRUE P.O.B. OF THE 8.62 ACRE TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS "S. BROSEMER" CAP HE SET AT 70.00' WEST AT THE APPARENT RIGHT-OF-WAY LINE OF COUNTY ROAD "F"
- 2) 590.19' NORTH TO THE NORTHEAST CORNER OF THE 8.62 ACRE TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS "S. BROSEMER" CAP HE SET AT 60.00' WEST AT THE APPARENT RIGHT-OF-WAY LINE OF COUNTY ROAD "F"
- 3) 2,572.19' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 2-20-10 ON THE TOWNSHIP LINE

WEST QUARTER CORNER 01-20-10