

NORTHWEST CORNER SECTION 03, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 41 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 4"** FOR THE CORNER TO SECTIONS 3 & 4-20-10 ON THE TOWNSHIP LINE.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 15" X 9" X 5" LIMESTONE THEY SET FOR THE NORTH 1/4 CORNER OF SECTION 3-20-10
 - 2) 80.00 CHAINS EAST ON THE TOWNSHIP LINE TO THE 24" X 20" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2 & 3-20-10
 - 3) 39.96 CHAINS SOUTH TO THE 29" X 17" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 4-20-10
 - 4) 79.96 CHAINS SOUTH TO THE 28" X 15" X 1-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-20-10

- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 158 DATED MAY 21, 1883 AT THE REQUEST OF McCORMICK TO ESTABLISH SECTION CORNERS IN SECTION 4-20-10, SAID THAT **HE FOUND THE STONE IN PLACE** AT THE NORTHEAST CORNER OF SECTION 4-20-10 ON THE TOWNSHIP LINE BY EXTENDING THE SECTION LINE FROM THE STONE THAT HE SET FOR THE SOUTHEAST CORNER OF SECTION 4-20-10 THROUGH THE STONE THAT HE FOUND AT THE EAST 1/4 CORNER OF SECTION 4-20-10, WITH THE TOWNSHIP LINE FROM THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 5-20-10 THROUGH THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 4-20-10 ON THIS **INFORMAL SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE NORTH 1/4 CORNER OF SECTION 4-20-10
 - 2) 80.00 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 4-20-10

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 268 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 22 TO 24 PETITIONED BY J. Y. SCHOECK AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 19-10 AND 20-10 [PACKET 517 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 16, 1884, WAS ESTABLISHED AS A **50 FOOT WIDE ROAD** ON JULY 12, 1884 AS NOTED BY JOHN L. BUTLER, CHAIRMAN PROTEM OF THE BOARD OF COUNTY COMMISSIONERS, AND ATTESTED BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 34-19-10 ON THE TOWNSHIP LINE ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 27-19-10 TO BEGIN THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 3-20-10 AT THE TERMINUS OF THIS ROAD ALLOWED BY THE VIEWERS
 - 3) THE ROAD PETITIONED FROM THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 3-20-10 EXTENDING SOUTH ON THE SECTION LINES TO THE SOUTHWEST CORNER OF SECTION 10-20-10 WAS **REJECTED** BY THE VIEWERS

- 4) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, BY C. P. COWEN, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 116, A **PERMANENT SURVEY** AT THE REQUEST OF GEORGE CRICKLAND TO ESTABLISH THE LINES AND CORNERS OF THE EAST 1/2 OF THE NORTHWEST 1/4 OF SECTION 6-20-11 RECORDED IN SURVEY BOOK "F" ON PAGE 132 DATED MAY 1-9, 1888, APPARENTLY DID **NOT**

FIND THE STONE AT THE NORTHWEST CORNER OF SECTION 3-20-10 ON THE TOWNSHIP LINE AS HE RAN THE TOWNSHIP LINE FROM THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 4-20-11 WEST TO THE STONE THAT HE FOUND IN THE GROUND IN GOOD CONDITION AT THE NORTH 1/4 CORNER OF SECTION 5-20-10. HE NOTED THAT THE TOTAL DISTANCE BETWEEN THESE TWO STONES WAS 36,867 FEET.

NORTHWEST CORNER SECTION 03-20-10