

**WEST 1/4 CORNER SECTION 04, TOWNSHIP 20 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 239 OF THE GLO ORIGINAL FILED NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 13" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 5-20-10 ON JUNE 20, 1857.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 40.10 CHAINS NORTH TO THE 20" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-20-10 ON THE TOWNSHIP LINE
  - 2) 40.00 CHAINS SOUTH TO THE 28" X 13" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-20-10
  
- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 102, AN **AGREEMENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 102 DATED MAY 25 & 26, 1885 FOR W. V. PHILLIPS, RADER, AND R. H. McCORMICK TO LOCATE THE CENTER CORNER AND THE LINES AND CORNERS OF THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 5-20-10, SAID THAT **HE SET A STAKE** FOR THE EAST 1/4 CORNER OF SECTION 5-20-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 5-20-10 ON THE TOWNSHIP LINE, AND THE LOCATION OF THE GOVERNMENT STONE AT THE SOUTHEAST CORNER OF SECTION 5-20-10 ON THIS **AGREEMENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION
  - 1) 2,644.5' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 5-20-10 ON THE TOWNSHIP LINE
  - 2) 2,644.5' SOUTH TO THE LOCATION FOR THE GOVERNMENT STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 5-20-10
  - 3) 1,316.5' WEST TO THE 4" X 7" X 16" STONE HE SET FOR THE SOUTHEAST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 5-20-10
  - 4) 2,633' WEST TO THE 5" X 9" X 14" STONE HE SET FOR THE CENTER CORNER OF SECTION 5-20-10

WEST QUARTER CORNER 04-20-10