

NORTH 1/4 CORNER SECTION 06, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 41 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 8" X 6"** FOR THE NORTH 1/4 CORNER OF SECTION 6-20-10 ON THE TOWNSHIP LINE.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING DISTANCES:

- 1) 40.50 CHAINS WEST ON THE TOWNSHIP LINE TO THE 28" X 9" X 4" LIMESTONE WITH A MOUND OF ROCK THEY SET FOR THE CORNER TO TOWNSHIPS 19 & 20 SOUTH, RANGES 9 & 10 EAST ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE
 - 2) 39.50* CHAINS EAST ON THE TOWNSHIP LINE TO THE 32" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-20-10 [***NOTE:** THIS DISTANCE SHOWS UP AS 40.00 CHAINS ON THE KANSAS SOCIETY OF LAND SURVEYORS DISC OF THE ORIGINAL FIELD NOTES – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 31 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 86 DATED JUNE 30, 1874 TO SUBDIVIDE THE SOUTHWEST 1/4 OF SECTION 31-19-10 BY A LINE NORTH & SOUTH INTO EAST AND WEST HALVES, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 31-19-10 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,320' WEST ON THE TOWNSHIP LINE TO THE 16" X 12" X 5" STONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 31-19-10
 - 2) 2,670' WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-19-10 AT THE TOWNSHIP CORNER ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 78, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 158 DATED JULY 14 & 15, 1903 AT THE REQUEST OF J. ROSECRANTS FOR A SURVEY FOR THE PURPOSE OF LOCATING AND PERMANENTLY ESTABLISHING THE CORNERS AND BOUNDARIES OF THE EAST 1/2 AND THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 31-19-10 AND RUN SUCH LINES AS ARE NECESSARY TO PROPERLY COMPLETE THE WORK, SAID THAT **HE FOUND THE STONE AT 20 LINKS EAST AND 31 LINKS SOUTH OF THE END OF A STONE WALL** AT THE SOUTH 1/4 CORNER OF SECTION 31-91-10 ON THE TOWNSHIP LINE ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 186 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 69" IN MISCELLANEOUS DRAWER NUMBER 3 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 20.03 CHAINS WEST ON THE TOWNSHIP LINE TO THE 18" X 6" X 4" STONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 31-19-10, AT 32 LINKS NORTH OF A HEDGE
- 2) 40.50 CHAINS WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 31-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE
- 3) 40.11 CHAINS EAST ON THE TOWNSHIP LINE TO THE STONE HE SET FOR THE PERMANENT SOUTHEAST CORNER OF SECTION 31-19-10, AS WITNESSED BY A "X" MARK HE MADE ON FLAT STONES 20 LINKS AND 33 LINKS SOUTH OF THE TRUE CORNER
- 4) 80.17 CHAINS EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 32-19-10

- 4) GREGORY A. MILES, L.S. 667, IN A SECTION CORNER REPORT DATED OCTOBER 8, 1982, FOR THIS CORNER 82-144, SURVEY F31001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE EAST HALF OF THE SOUTHWEST QUARTER OF SECTION 31-19-10, SAID THAT HE DUG FOR THE STONE AT THIS CORNER WITH A COUNTY MAINTAINER. **HE FOUND THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 31-91-10 ON THE TOWNSHIP LINE THAT WAS SET BY ALVA J. SMITH IN A 1903 SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 158. HE SET A 5/8" REBAR WITH A LYON COUNTY CAP UNDER THE STONE, AND A 5/8" REBAR WITH A LYON COUNTY CAP ON THE WEST SIDE OF THE STONE.**
- 1) 69.4' ENE TO A NAIL IN THE NORTH SIDE OF A TELEPHONE POLE
 - 2) 35.95' ESE TO A NAIL IN THE WEST SIDE OF A POWER POLE
 - 3) 20.25' SOUTH TO A NAIL IN THE TOP OF A CORNER FENCE POST
 - 4) 28.30' WSW TO A NAIL IN THE TOP OF A FENCE POST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,321.36' WEST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE E/12 OF THE SW1/4 OF SECTION 31-19-10
 - 2) 2,635.32' NORTH TO THE 1/2" REBAR HE SET FOR THE CENTER CORNER OF SECTION 31-19-10
- 5) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED OCTOBER 31, 1997, FOR JOB NUMBER 97295-02 FOR LYON COUNTY BRIDGE REPLACEMENT PROJECT NUMBER 97-8U, SAID THAT **HE FOUND THE STONE WITH A 5/8" REBAR WITH A LYON COUNTY CAP ON THE WEST SIDE OF THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 31-19-10 ON THE TOWNSHIP LINE FROM EXISTING REFERENCES ON FILE IN THE COUNTY ENGINEER'S OFFICE.
- 1) 17.50' SOUTH TO A 40 D SPIKE IN THE TOP OF A CORNER FENCE POST
 - 2) 28.60' SW TO A 40 D SPIKE IN THE TOP OF A CORNER FENCE POST
 - 3) 29.30' NE TO A 40 D SPIKE IN AN 8" DIAMETER LOCUST TREE
 - 4) 35.40' SE TO A 40 D SPIKE IN A POWER POLE
 - 5) A STONE IS 1,321.89' WEST [20.03 CHAINS PER SMITH'S CALL]
- HIS DRAWING ON HIS REFERENCE REPORT SHOWS THE FOLLOWING:
- 1) 2,672.92' WEST ON THE TOWNSHIP LINE TO THE SOUTHWEST CORNER OF SECTION 31-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED JANUARY 15, 2009 FOR PROJECT NUMBER 08376-02, SURVEY F32001 IN THE SURVEY FILE FOR TOWNSHIP 19-10 FOR A SURVEY OF THE NORTH 495 FEET OF THE NORTHWEST QUARTER OF SECTION 31-19-10 FOR CRESS/BEYER, SAID THAT **HE FOUND THE 5/8" REBAR OVER THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 31-19-10 ON THE TOWNSHIP LINE FROM HIS EXISTING REFERENCES ON FILE AT THE STATE HISTORICAL SOCIETY IN OCTOBER 1997. **[NOTE: DEPUTY BROSEMER INFORMED ME THAT HE DUG UP THE STONE AND HE PLACED THE ABOVE 5/8" REBAR OVER THE TOP OF THE STONE - WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]**
- 1) 17.5' SOUTH TO A 40 D SPIKE IN THE TOP OF A CORNER FENCE POST
 - 2) 28.6' SW TO A 40 D SPIKE IN THE TOP OF A CORNER FENCE POST
 - 3) 29.3' NE TO A 40 D SPIKE IN A 12" DIAMETER LOCUST TREE
 - 4) 35.4' SE TO A 40 D SPIKE IN A POWER POLE
 - 5) IN LINE WITH A FENCE TO THE NORTH AND SOUTH [EXTENDED]
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,672.58' WEST ON THE TOWNSHIP LINE TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SW 1/4 OF SECTION 31-19-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE [PRIOR SURVEY = 2,672.91'] **[NOTE: HE REFERENCE REPORT STATES A 5/8" REBAR**

WITH A LYON COUNTY CAP AT THE SOUTHWEST CORNER OF SECTION 31-19-10
– WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]

- 2) 2,645.40' EAST ON THE TOWNSHIP LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 32-19-10
- 3) 5,287.50' EAST ON THE TOWNSHIP LINE TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 32-19-10
- 4) 6,603.73' EAST ON THE TOWNSHIP LINE TO EDMISTON'S STONE HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF THE SE1/4 OF SECTION 32-19-10
- 5) 2,632.61' NORTH TO THE 1/2" REBAR WITH A "MILES" CAP HE FOUND AT THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 32-19-10
- 6) 5,268.73' NORTH TO THE 1" PIN & STONE HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 32-19-10

NORTH QUARTER CORNER SECTION 06-20-10