

NORTH 1/4 CORNER SECTION 08, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 244 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 15" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 8-20-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.95 CHAINS WEST TO THE 19" X 13" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-20-10
 - 2) 39.95 CHAINS EAST TO THE 28" X 13" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-20-10

- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 158 DATED MAY 21, 1883 AT THE REQUEST OF McCORMICK TO ESTABLISH SECTION CORNERS IN SECTION 4-20-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 5-20-10 ON THIS **INFORMAL SURVEY**. HE USED THIS STONE AND THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 4-20-10 TO SET THE SOUTHWEST CORNER OF SECTION 4-20-10 AND THE SOUTH 1/4 CORNER OF SECTION 4-20-10.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.92 CHAINS EAST TO THE STONE HE SET FOR THE SOUTHWEST CORNER OF SECTION 4-20-10
 - 2) 79.86-1/2 CHAINS WEST TO THE STONE HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 4-20-10
 - 3) 119.81 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 4-20-10

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 102, AN **AGREEMENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 102 DATED MAY 25 & 26, 1885 FOR W. V. PHILLIPS, RADER, AND R. H. McCORMICK TO LOCATE THE CENTER CORNER AND THE LINES AND CORNERS OF THE WEST 1/2 OF THE NORTHEAST 1/4 OF SECTION 5-20-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 5-20-10 ON THIS **AGREEMENT SURVEY**.

NORTH QUARTER CORNER 08-20-10