

NORTH 1/4 CORNER SECTION 10, TOWNSHIP 20 SOUTH, RANGE 10 EAST

- 1) ON PAGE 235 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 16" X 1-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 10-20-10 ON JUNE 19, 1857. THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.85 CHAINS WEST TO THE 28" X 15" X 1-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-20-10
 - 2) 39.84 CHAINS EAST TO THE 24" X 21" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-20-10

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 82 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 139 DATED AUGUST 15, 1875 TO ESTABLISH THE CORNERS TO THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 3-20-10, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 3-20-10 ON THIS **PERMANENT SURVEY**. HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,309-1/4' WEST TO THE 16" X 10" X 5" STONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 3-20-10
 - 2) 2,618-1/2' WEST TO THE 34" X 8" X 6" STONE HE SET FOR THE PERMANENT SOUTHWEST CORNER OF SECTION 3-20-10

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 14, 2001, FOR JOB NUMBER 01577-02, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 10-20-10, AND **NO EVIDENCE** OF THE MONUMENT WAS FOUND. HE DID **NOT** RESET THE NORTH 1/4 CORNER OF SECTION 10-20-10 ON THIS SURVEY, BUT HE STATED "THE EAST-WEST POSITION OF FENCES TO THE NORTH AND TO THE SOUTH ARE REASONABLE."

- 4) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 19, 2015, FOR PROJECT NUMBER 15181-02, THE SURVEY OF TWO TRACTS IN THE NORTHWEST 1/4 OF SECTION 10-20-10 FOR LAMBERT/DOTY, SURVEY F10001 IN THE SURVEY FILE FOR TOWNSHIP 20-10, SAID THAT HE CONSIDERED THE NORTH 1/4 CORNER OF SECTION 10-20-10 BOTH **LOST** AND **OBLITERATED**. HE NOTED THAT HE HAD PREVIOUSLY EXCAVATED FOR THIS CORNER IN 2001 AND THE STONE WAS **NOT** FOUND. HE RESET THIS CORNER ON LINE FROM THE NORTHWEST CORNER OVER THE NORTH 1/16TH CORNER OF THE NORTHWEST 1/4 AND IN LINE WITH A FENCE TO THE NORTH EXTENDED. **HE SET A 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP** FOR THE NORTH 1/4 CORNER OF SECTION 10-20-10
 - 1) IN LINE WITH A FENCE TO THE NORTH EXTENDED
 - 2) 1' EAST TO A LINE OF FENCE TO THE SOUTH EXTENDED
 - 3) 20.7' NORTH TO A CONCRETE NAIL & BOTTLECAP IN A CORNER POST
 - 4) 23.85' SOUTH TO THE NEAR FACE OF A PIPE CORNER POST
 - 5) 33.6' SW TO A CONCRETE NAIL & BOTTLECAP IN THE WEST GATE POST
 - 6) 70.7' SW TO A 40 D NAIL & BOTTLECAP IN A POWER POLE
 - 7) IN THE TRAVELED WAY OF GRAVEL COUNTY ROAD 120 EAST-WESTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,314.61' WEST TO THE 1/2" IRON PIN HE FOUND AT THE NORTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 10-20-10
 - 2) 1,570.38' WEST TO THE RAILROAD SPIKE HE SET FOR THE CORNER TO THE WEST TRACT AND THE EAST TRACT

HIS INFORMATION IS CONTINUED ON PAGE 2

- 3) 2,623.38' WEST TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 10-20-10
- 4) 2,632.57' EAST TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 10-20-10
- 5) 2,641.50' SOUTH TO THE 5/8" X 24" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 10-20-10
- 6) 5,285.94' SOUTH TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 10-20-10

NORTH QUARTER CORNER 10-20-10